

Synspective SAR DATA PRODUCT FORMAT MANUAL

Version 19.0
Apr 2, 2026

© 2022 - 2026 Synspective Inc



Revision History

| Version | Date | Description |
|---------|--------------|---|
| v1.0 | Nov 17, 2022 | Initial version |
| v2.0 | Dec 15, 2022 | <ol style="list-style-type: none"> 1. BRS File name is changed to match with IMG File name (Table 1.1-1) 2. Scene ID and Product ID in VOL File and summary.txt are changed to match with IMG File name (No. 9 and 12 in Table 1.1-7/ No. 9 in Table 1.1-9/ No. 2 and 3 in Table 1.1-18) 3. The sign for left and right looking direction is fixed (No.39 in Table 1.1-9) 4. The description of Synsperspective products specific implementation in SICD product is added (Table 1.2-2) 5. Orbit state vectors are added in XML Metadata for GRD product (“stateVecFormat” ~ “velZ” in Table 2.1-2) 6. Section number for the reference in Calibration Factor's Description in XML metadata data for GRD is updated (“calibrationFactor” in Table 2.1-2) 7. StriX-1 is added for Radiometric Calibration (Section 4) 8. “Intensity conversion factor” is changed to “Calibration factor” (Table 4-1) 9. Calibration factor (CF) subscripts (CF_{SLC CEOS} and CF_{GRD}) are added (Section 4) 10. New product version is added in product version history (Table 5-1) |
| v3.0 | Feb 27, 2023 | <ol style="list-style-type: none"> 1. Datetype for No. 90 (Bandwidth per look in the range direction) in Data Set Summary Records in CEOS is updated from F16.7 to F16.6 (Table 1.1-9) 2. New product version is added in product version history (Table 5-1) |
| v4.0 | May 15, 2023 | <ol style="list-style-type: none"> 1. Updated description of GRD Product (Section 2) 2. Updated eop:referenceSystemIdentifier Description to “Projection coordinate system ID (EPSG Geodetic Parameter Dataset)” and changed its example to “epsg:32630 (UTM zone 30N)” (Table 2.1-2) 3. Updated eop:mapProjection Description to “Map projection” and changed its example to “UTM” (Table 2.1-2) 4. Updated GeoTIFF Tag GeoAsciiParamsTag Description/Example to: “Based on GeoTIFF standards: “WGS 84 / UTM zone 18S WGS 84 ” (Table 2.1-3) 5. Updated GeoTIFF Tag ModelPixelScaleTag Description/Example to: “Pixel spacing (meters)” (Table 2.1-3) 6. Updated GeoTIFF Tag GTCitationGeoKey Description/Example to: “WGS 84 / UTM zone 18S” (Table 2.1-3) 7. Updated GeoTIFF Tag GTCitationGeoKey Description/Example to: “WGS 84 / UTM zone 18S” (Table 2.1-3) 8. New product version is added in product version history (Table 5-1) 9. Fixed links to Reference |
| v5.0 | June 5, 2023 | <ol style="list-style-type: none"> 1. Added the description of New Product SR-GRD (Section 3) |
| v6.0 | Aug 1, 2023 | <ol style="list-style-type: none"> 1. Added NESZ information to GRD and SR-GRD XML (Table 2.1-2) 2. Added Sliding Spotlight mode to SR-GRD product (Section 2) 3. New product version is added in product version history (Table 5-1) |
| v7.0 | Oct 2, 2023 | <ol style="list-style-type: none"> 1. Updated the description of Field No.25 Data Set summary Records to: “reference height above the ellipsoid” (Table 1.1-9) for CEOS products 2. New product version is added in product version history (Table 5-1) |
| v7.1 | Oct 19, 2023 | <ol style="list-style-type: none"> 1. New product version is added in product version history (Table 5-1) |

| Version | Date | Description |
|---------|--------------|--|
| v7.2 | Dec 6, 2023 | <ol style="list-style-type: none"> Updated the remarks of Field No.24 Facility Related Data Record (Table 1.1-14) for CEOS products New product version is added in product version history (Table 5-1) |
| v8.0 | Jan 22, 2024 | <ol style="list-style-type: none"> Updated the Description of Field No.22 and 23 Facility Related Data Record (Table 1.1-14) for CEOS products Updated SICD format standards from NGA.STND.0024-1_1.2.1 to NGA.STND.0024-1_1.3.0 (Section 1.2) Added SICD format standards reference, NGA.STND.0024-2_1.3.0 and NGA.STND.0024-3_1.3.0 (Section 1.2) Changed eop:processorName from StrixProcessor to GrdProcessor in XML metadata for GRD and SR-GRD product (Table 2.1-2). New product version is added in product version history (Table 5-1) Updated reference for SICD formats ([2], [3] and [4] in Reference) |
| v8.1 | Jan 23, 2024 | <ol style="list-style-type: none"> New product version is added in product version history (Table 5-1) |
| v8.2 | Mar 18, 2024 | <ol style="list-style-type: none"> Corrected a reference number for radiometric calibration in SICD format (Section 4) New product version is added in product version history (Table 5-1) |
| v8.3 | Apr 10, 2024 | <ol style="list-style-type: none"> New product version is added in product version history (Table 5-1) |
| v9.0 | Apr 22, 2024 | <ol style="list-style-type: none"> New product version is added in product version history (Table 5-1) |
| v9.1 | May 15, 2024 | <ol style="list-style-type: none"> Added Strix-3 for Satellite type Consolidated GRD and SR-GRD sections (Section 2) Updated radiometric calibration table (Table 4-1) New product version is added in product version history (Table 5-1) |
| v10.0 | Aug 1, 2024 | <ol style="list-style-type: none"> Removed "Blank" in remarks of Field No. 17 and 18 Data Quality Summary Record (Table 1.1-13) Added new fields No.6 and 7, Pds_SlantRangeResolution and Pds_AzimuthResolution, in Summary Information (Table 1.1-18) Restructure XML metadata table (Table 2.1-2) Added new fields about range and azimuth resolution in XML metadata in GRD and SR-GRD product (Table 2.1-2) Changed the title of Section 5 to "Product Release History" from "Product Version History" Added Table 5-3 Software version related fields Added thumbnail image in SICD product format (Section 1.2.1 and 1.2.4) Added thumbnail image in GRD and SR-GRD product format (Section 2.1.1 and 2.1.4) |
| v10.1 | Aug 22, 2024 | <ol style="list-style-type: none"> New version is added to product release history (Table 5-1) |
| v10.2 | Sept 4, 2024 | <ol style="list-style-type: none"> New version is added to product release history (Table 5-1) |
| v10.3 | Oct 2, 2024 | <ol style="list-style-type: none"> Added Staring Spotlight Added Note in Radiometric Calibration (Section 4) about Staring Spotlight. New version is added to product release history (Table 5-1) |
| v11.0 | Nov 12, 2024 | <ol style="list-style-type: none"> Added StriX-4 Added Cloud Optimized GeoTIFF (COG) in GRD and SR-GRD product (Section 2) |

| Version | Date | Description |
|---------|---------------|---|
| | | <ol style="list-style-type: none"> Removed Note in Radiometric Calibration (Section 4) about Staring Spotlight. New version is added to product release history (Table 5-1) |
| v12.0 | Dec 3, 2024 | <ol style="list-style-type: none"> Added note in Radiometric Calibration (Section 4) about SR-GRD. New version is added to product release history (Table 5-1) |
| v13.0 | Jan 14, 2025 | <ol style="list-style-type: none"> New version is added to product release history (Table 5-1) |
| v14.0 | Mar 25, 2025 | <ol style="list-style-type: none"> Added StriX-2 New version is added to product release history (Table 5-1) Changed the cover page and the colors of the tables |
| v14.1 | Apr 2, 2025 | <ol style="list-style-type: none"> New version is added to product release history (Table 5-1) |
| v15.0 | June 25, 2025 | <ol style="list-style-type: none"> New version is added to product release history (Table 5-1) |
| v15.1 | July 15, 2025 | <ol style="list-style-type: none"> New version is added to product release history (Table 5-1) |
| v16.0 | Sept 30, 2025 | <ol style="list-style-type: none"> Removed signs of the offnadir angle in CEOS metadata , Img_OffNadirAngle in Contents of Summary Information(Table 1.1-18) and No.135 Data Set Summary Records (Table 1.1-9) Switched thumbnail images pixel-intensity mapping from linear to logarithmic in SICD and CEOS Updated the description of Satellite heading angle in GRD XML Metadata (Table 2.1-2) New version is added to product release history (Table 5-1) |
| v17.0 | Dec 9, 2025 | <ol style="list-style-type: none"> Updated descriptions of Thumbnail Image for CEOS, SICD and GRD (Section 1.1.7, 1.2.4 and 2.1.4) Updated descriptions of Quicklook raster data for GRD product (Section 2.1.5) Changed Standard GeoTIFF format to Cloud Optimized GeoTIFF for GRD Product (Section 2.1.1) Changed a file naming convention for quicklook raster image in GRD product (Table 2.1-1) Changed a format of software version in GRD XML Metadata, eop:processorVersion (Table 2.1-2) Updated GeoTIFF tags (Table 2.1-3) Updated the note for GRD GeoTIFF calibration (Section 4) New version is added to product release history (Table 5-2) |
| v17.1 | Dec 17, 2025 | <ol style="list-style-type: none"> New version is added to product release history (Table 5-2) |
| v17.2 | Jan 7, 2026 | <ol style="list-style-type: none"> New version is added to product release history (Table 5-2) |
| v17.3 | Feb 10, 2026 | <ol style="list-style-type: none"> New version is added to product release history (Table 5-2) |
| v17.4 | Feb 16, 2026 | <ol style="list-style-type: none"> Added StriX-5 New version is added to product release history (Table 5-2) |
| v18.0 | Mar 11, 2026 | <ol style="list-style-type: none"> Added number of azimuth and range looks in in GRD XML (Table 2.1-2) Added temporal metadata file in SICD (Section 1.2.1) and GRD (Section 2.1.1) products New version is added to product release history (Table 5-2) |

| Version | Date | Description |
|----------------|--------------|--|
| v18.1 | Mar 17, 2026 | 1. New version is added to product release history (Table 5-2) |
| v18.2 | Mar 24, 2026 | 2. New version is added to product release history (Table 5-2) |
| v19.0 | Apr 2, 2026 | 1. A new product, Orthorectified (ORT), has been added to Section 3 . 2. The former Section 3 (Radiometric Calibration) has been moved to Section 4. 3. The former Section 4 (Product Release History) is now Section 5. |

Table of contents

| | |
|--|-----------|
| Revision History | 1 |
| Introduction | 7 |
| 1. SLC Product | 7 |
| 1.1 CEOS Product Format | 7 |
| 1.1.1 Product Composition | 7 |
| Table 1.1-1 SLC CEOS Product File Naming Convention | 8 |
| 1.1.2 Product Record Description | 8 |
| Table 1.1-2 Record Structure SLC CEOS Format | 9 |
| 1.1.3 Record Data Type | 9 |
| Table 1.1-3 Data Type | 9 |
| 1.1.4 Record Type Code and Record Subtype Code | 10 |
| Table 1.1-4 Record Type of Each Record | 10 |
| 1.1.5 Contents of Records in SLC CEOS Files | 10 |
| Table 1.1-5 Volume Descriptor Record | 10 |
| Table 1.1-6 File Pointer Record | 11 |
| Table 1.1-7 Text Record | 13 |
| Table 1.1-8 Leader File Descriptor Record | 14 |
| Table 1.1-9 Data Set Summary Records | 15 |
| Table 1.1-10 Platform Position Data Record | 22 |
| Table 1.1-11 Attitude Data Record | 23 |
| Table 1.1-12 Radiometric Data Records | 24 |
| Table 1.1-13 Data Quality Summary Record | 25 |
| Table 1.1-14 Facility Related Data Record | 26 |
| Table 1.1-15 Image File Descriptor Record | 28 |
| Table 1.1-16 Signal Data Records | 30 |
| Table 1.1-17 Trailer Descriptor Record | 32 |
| 1.1.6 Summary Information | 34 |
| Table 1.1-18 Contents of Summary Information | 34 |
| 1.1.7 Thumbnail Image | 36 |
| 1.2 SICD Product Format | 37 |
| 1.2.1 Product Composition | 37 |
| Table 1.2-1 SLC SICD product file naming convention | 37 |
| 1.2.2 SICD XML Metadata | 38 |
| Table 1.2-2 XML Field for Synspective products specific implementation in SICD product | 38 |
| 1.2.3 NITF Metadata | 38 |
| 1.2.4 Thumbnail Image | 38 |
| 2. GRD and SR-GRD Product | 39 |

| | |
|---|-----------|
| 2.1 GeoTIFF + XML Product Format | 39 |
| 2.1.1 Product Composition | 39 |
| Table 2.1-1 GRD Product File Naming Convention | 40 |
| 2.1.2 XML Metadata | 41 |
| Table 2.1-2 GRD XML Tag and Attribute Name | 41 |
| 2.1.3 GeoTIFF Tag | 45 |
| Table 2.1-3 GeoTIFF Tag | 46 |
| 2.1.4 Thumbnail Image | 46 |
| 2.1.5 Quicklook raster data (COG) | 47 |
| 3. ORT Product | 48 |
| 3.1 GeoTIFF + XML Product Format | 48 |
| 3.1.1 Product Composition | 48 |
| Table 3.1-1 ORT Product File Naming Convention | 49 |
| 3.1.2 XML Metadata | 50 |
| Table 3.1-2 ORT XML Metadata Tag and Attribute Name | 50 |
| 3.1.3 GeoTIFF Tag | 56 |
| Table 3.1-3 ORT GeoTIFF Tag | 56 |
| Table 3.1-4 ORT GeoTIFF GeoKey Directory | 58 |
| 3.1.4 COG Layer Specifications | 58 |
| Table 3.1-5 ORT COG File Specifications | 59 |
| 3.1.5 Thumbnail Image | 60 |
| 4. Radiometric Calibration | 61 |
| Table 4-1 Radiometric Correction | 61 |
| 5. Product Release History | 63 |
| Table 5-1 Product release history | 63 |
| Table 5-2 Product release history (after Dec 9, 2025) | 65 |
| Table 5-3 Software version related fields | 66 |
| Reference | 67 |

Introduction

This document defines the format of Synspective SAR data products observed by StriX satellites (Synspective products). There are four types of Synspective products: Single Look Complex (SLC), Ground Range Detected (GRD), Super Resolution GRD (SR-GRD) and Orthorectified (ORT). SLC products are available in CEOS and SICD formats. GRD, SR-GRD and ORT products are available in Cloud Optimized GeoTIFF (COG) + XML format.

1. SLC Product

The general specification of the SLC product:

- Single Look Complex (SLC) data after range and azimuth compression
- single look in azimuth and range
- provided in slant range geometry
- phase information is preserved
- pixel spacing is in slant geometry
- data type: 32 bit float (I) + 32 bit float (Q)
- mode of observation: Stripmap, Sliding Spotlight or Staring Spotlight
- single polarization: VV

1.1 CEOS Product Format

CEOS standard format was published in 1988 and does not specify the naming convention. In practice, Synspective's CEOS product format references the ALOS-2 PALSAR-2 CEOS format [\[1\]](#).

1.1.1 Product Composition

SLC CEOS format is a wrapper, which combines multiple files:

- Volume directory file (VOL),
- SAR leader file (LED),
- SAR image data (IMG),
- SAR trailer file (TRL)

CEOS product includes the following files as well.

- Summary information
- Thumbnail image

The naming convention for SLC CEOS product files are described in the table below.

Table 1.1-1 SLC CEOS Product File Naming Convention

| File Type | Number of Files | File Name | Record Name | Contents |
|-----------------------|-----------------|--|---|--|
| Volume Directory File | 1 | VOL-<Scene ID> -<Product ID> | - Volume descriptor File Pointer | This stores the volume and file management information. |
| SAR Leader File | 1 | LED-<Scene ID> -<Product ID> | - File descriptor - Data set summary - Platform location data - Attitude data - Radiometric data - Data quality summary - Facility related data | This file stores information such as annotation data and ancillary data related to the image data. |
| SAR Image Data | 1 | IMG-<Polarization> -<Scene ID>-<Product ID> | - File descriptor - Signal data | This file stores image data. |
| SAR Trailer File | 1 | TRL-<Scene ID> -<Product ID> | - File descriptor | This file stores the final information about the image data. |
| Summary Information | 1 | summary.txt | | |
| Thumbnail Image | 1 | BRS-<Polarization> -<Scene ID> -<Product ID>.png | | |

where:

Scene ID = AAAAAA-YYYYMMDDThhmmssZ

AAAAAA : Satellite type

- STRIXA: StriX- α
- STRIXB: StriX- β
- STRIX1 ~ N: StriX-1 ~ N

○ Example:

- STRIX1: StriX-1
- STRIX2: StriX-2

- : Separator

YYYYMMDD: Scene center observation date (YYYY: year, MM: month, DD: day)

hhmmss: Scene center observation time* (hh: hour, mm: minutes, ss: seconds)

*precise orbit is used when available

Product ID = DDEEE

DD: Observation mode

- SM: Stripmap mode
- SL: Sliding Spotlight mode
- ST: Staring Spotlight mode

EEE: Processing level (SLC: Single Look Complex)

1.1.2 Product Record Description

The table below shows SLC CEOS format record structure.

Table 1.1-2 Record Structure SLC CEOS Format

| Record No. | Record Length [byte] | Number of Record | Record Name | File Name |
|------------|----------------------|------------------|-----------------------------|-----------------------|
| 1 | 360 | 1 | Volume descriptor | Volume Directory File |
| 3 | 360 | 3 | File pointer | |
| 4 | 360 | 1 | Text | |
| 1 | 720 | 1 | SAR Leader file descriptor | SAR Leader File |
| 2 | 4,096 | 1 | Dataset summary | |
| 3 | 4,680 | 1 | Platform location data | |
| 4 | 16,384 | 1 | Attitude data | |
| 5 | 9,860 | 1 | Radiometric data | |
| 6 | 1,620 | 1 | Data quality summary | |
| 7 | 5000 | 1 | Facility related data | |
| 1 | 720 | 1 | SAR data file descriptor | SAR Image Data |
| 2 to n+1 | variable | n | Signal data | |
| 1 | 720 | 1 | SAR trailer file descriptor | SAR Trailer |

1.1.3 Record Data Type

The definition of data type is shown in the table below.

Table 1.1-3 Data Type

| Type (code) | Details |
|-------------|--|
| Am | ASCII character (Left fill if not specified) |
| Im | Integer number in ASCII form (Right fill) |
| Fm.n | Floating number in ASCII form (Right fill) |
| Em.n | Exponential number in ASCII form (Right fill) |
| Bm | Binary number (the first byte is the most significant, big endian) |

where:

m : Number of digits

n : Number of decimal places

1.1.4 Record Type Code and Record Subtype Code

Each record has record type code and record subtype code to distinguish each other. Each record type is shown in the table below.

Table 1.1-4 Record Type of Each Record

| Record Name | First Record Type | Record Type | Second Record Type | Third Record Type | Record Length [bytes] |
|-----------------------------|-------------------|-------------|--------------------|-------------------|-----------------------|
| Volume descriptor | 192 | 192 | 18 | 18 | 360 |
| File pointer | 219 | 192 | 18 | 18 | 360 |
| Text | 18 | 192 | 18 | 18 | 360 |
| SAR Leader file descriptor | 11 | 192 | 18 | 18 | 720 |
| Dataset summary | 18 | 10 | 18 | 20 | 4096 |
| Platform location data | 18 | 30 | 18 | 20 | 4680 |
| Attitude data | 18 | 40 | 18 | 20 | 16384 |
| Radiometric data | 18 | 50 | 18 | 20 | 9860 |
| Data quality summary | 18 | 60 | 18 | 20 | 1620 |
| Facility related data | 18 | 200 | 18 | 70 | 5000 |
| SAR data file descriptor | 50 | 192 | 18 | 18 | 720 |
| Signal data | 50 | 10 | 18 | 20 | Variable |
| SAR trailer file descriptor | 63 | 192 | 18 | 18 | 720 |

1.1.5 Contents of Records in SLC CEOS Files

The record formats are shown in the tables below.

Table 1.1-5 Volume Descriptor Record

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|---------------------------------------|
| 1 | 1-4 | B4 | Record Number = 1 |
| 2 | 5 | B1 | First subtype code = 192 |
| 3 | 6 | B1 | Record type code = 192 |
| 4 | 7 | B1 | Second subtype code = 18 |
| 5 | 8 | B1 | Third subtype code = 18 |
| 6 | 9-12 | B4 | Record length = 360 |
| 7 | 13-14 | A2 | ASCII/EBCDIC flag = 'Ab' : ASCII |
| 8 | 15-16 | A2 | Blank |
| 9 | 17-28 | A12 | Format descriptor ID = 'CEOS-SARbbbb' |

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|--|
| 10 | 29-30 | A2 | Revision level of the document = 'bA', 'bB', ... |
| 11 | 31-32 | A2 | Superstructure format revision level = 'bA', 'bB', ... |
| 12 | 33-44 | A12 | Software release and revision number = 'NNN.NNNbbbb' |
| 13 | 45-60 | A16 | Physical Volume ID = 'SYNSbbbbbbbbbb' |
| 14 | 61-76 | A16 | Logical volume ID = 'MMMMMYYYYmmDD' MMMMM = Mission name ('STRIX') N = Mission ID (Alpha='A', Beta='B', 1='1', 2='2', ...) YYYY = Product creation year mm = Product creation month DD = Product creation day |
| 15 | 77-92 | A16 | Volume set ID = 'MMMMMMbbbbbbbb' MMMMMM = Mission name ('Strix-A', 'Strix-B', 'Strix-1', 'Strix-2', ...) |
| 16 | 93-94 | I2 | Number of physical volumes in the logical volume = 'b1' |
| 17 | 95-96 | I2 | First tape's sequence number of the physical volume = 'b1' |
| 18 | 97-98 | I2 | Last tape's sequence number of the physical volume = 'b1' |
| 19 | 99-100 | I2 | Current tape's sequence number of the physical volume = 'b1' |
| 20 | 101-104 | I4 | Number of files in the logical volume following the volume directory file = 'bbb3': |
| 21 | 104-108 | I4 | Number of logical volumes in the volume set = 'bbb1' |
| 22 | 109-112 | I4 | Number of logical volumes in a physical volume = 'bbb1' |
| 23 | 113-120 | A8 | Logical volume creation date = 'YYYYMMDD' (without zero suppression) YYYY: Year ('0001'-'9999') MM: Month ('01'-'12') DD: Day ('01'-'31') |
| 24 | 121-128 | A8 | Logical volume creation time = 'HHMMSSXX' (without zero suppression) HH: Hour ('00'-'23') MM: Minute ('00'-'59') SS: Second ('00'-'59') XX: 10 milliseconds ('00'-'99') |
| 25 | 129-140 | A12 | Logical volume creation country (Japan) = 'JAPANbbbbbb' |
| 26 | 141-148 | A8 | Logical volume creator = 'SYNSbbbb' |
| 27 | 149-160 | A12 | Logical volume creation facility = 'SYNSbbbbbb' |
| 28 | 161-164 | I4 | Number of file pointer records in the volume directory = 'bbb3' |
| 29 | 165-168 | I4 | Number of text records in the volume directory = 'bbb1' |
| 30 | 169-260 | A92 | Volume descriptor spare area = blank |
| 31 | 261-360 | A100 | Private fields = blank |

Table 1.1-6 File Pointer Record

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|-------------------|
| 1 | 1-4 | B4 | Record Number = 1 |

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|--|
| 2 | 5 | B1 | First subtype code = 219 |
| 3 | 6 | B1 | Record type code = 192 |
| 4 | 7 | B1 | Second subtype code = 18 |
| 5 | 8 | B1 | Third subtype code = 18 |
| 6 | 9-12 | B4 | Record length = 360 |
| 7 | 13-14 | A2 | ASCII/EBCDIC flag = 'Ab'; ASCII |
| 8 | 15-16 | A2 | Blank |
| 9 | 17-20 | I4 | Reference file number Leader file = 'bbb1' Image file = 'bbb2' Trailer file = 'bbb3' |
| 10 | 21-36 | A16 | Reference file ID = 'MMMMNtFFFFbbbb' MMMM: Mission name ('STRIX') N: Mission number (Alpha = 'A', Beta = 'B', 1 = '1', 2 = '2', ...) T: Processing level code ('B' indicates SLC product) FFFF: File type 'SARL': Leader file 'IMOP': Image file 'SART': Trailer file |
| 11 | 37-64 | A28 | Reference file class ='SARLEADERbFILEbbbbbbbbbbbb': For leader file ='IMAGERYbOPTIONSbFILEbbbbbbbb': For image file ='SARTRAILERbFILEbbbbbbbbbbbb': For trailer file |
| 12 | 65-68 | A4 | Reference file class code ='SARL': For leader files ='IMOP': For image files ='SART': For trailer files |
| 13 | 69-96 | A28 | Reference file data type = 'MIXEDbBINARYbANDBASCIIbbbbbb' |
| 14 | 97-100 | A4 | Reference file data type code = 'MBAA' |
| 15 | 101-108 | I8 | Number of records in the reference file (zero suppression) Leader file = 'bbbbbb7' (SLC) Image file = number of SAR data records + 1 Trailer file = 'bbbbbb1' |
| 16 | 109-116 | I8 | Length of the first record in reference file = 'bbbb720' |
| 17 | 117-124 | I8 | Maximum record length (byte length) of the reference file: 'bbLLLL' |
| 18 | 125-136 | A12 | Reference file record length type ='VARIABLEbLEN': For leader files ='VARIABLEbLEN': For image files ='VARIABLEbLEN': For trailer files |
| 19 | 137-140 | A4 | Reference file record length type code ='VARE': For leader files ='VARE': For image files ='VARE': For trailer files |
| 20 | 141-142 | I2 | The number of the physical volume set containing the first record of the file = 'b1' |

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|---|
| 21 | 143-144 | I2 | The number of the physical volume set containing the last record of the file = 'b1' |
| 22 | 145-152 | I8 | Record number of the first record on this physical volume ='bbbbbbb1' |
| 23 | 153-160 | I8 | Record number of the last record on this physical volume Leader file ='bbbbbbb7' (SLC) Image file = number of lines + 1 Trailer file ='bbbbbbb1' |
| 24 | 161-260 | A100 | Blank |
| 25 | 261-360 | A100 | Private fields = blank |

Table 1.1-7 Text Record

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|--|
| 1 | 1-4 | B4 | Record Number = 5 |
| 2 | 5 | B1 | First subtype code = 18 |
| 3 | 6 | B1 | Record type code = 192 |
| 4 | 7 | B1 | Second subtype code = 18 |
| 5 | 8 | B1 | Third subtype code= 18 |
| 6 | 9-12 | B4 | Record length = 360 |
| 7 | 13-14 | A2 | ASCII/EBCDIC flag = 'Ab' In case of ASCII |
| 8 | 15-16 | A2 | Blank |
| 9 | 17-56 | A40 | Deliverable ID (Product ID) ='PRODUCT: DDEEEb ~ b' DD: Observation mode SL: Sliding Spotlight mode SM: Stripmap mode ST: Staring Spotlight mode EEE: Processing level SLC: Single Look Complex |
| 10 | 57-116 | A60 | Product creation location / date / time (without zero suppression) ='PROCESS: JAPAN-SYNS-STRIXNbYYYYMMDDbHHMMSSb ~ b' N: A, B, 1, 2, ... YYYYMMDD: Creation date HHMMSS: Creation time (UTC) |
| 11 | 117-156 | A40 | Physical tape ID ='TAPEbID: b ~ b' |
| 12 | 157-196 | A40 | Scene ID ='ORBITb: AAAAAA-YYYYMMDDThhmmssZb ~ b' AAAAAA: Satellite type ('STRIXN') N: A, B, 1, 2, ... YYYYMMDD: Scene center observation date (YYYY: year, MM: month, DD: day) hhmmss: Scene center observation time (hh: hour, mm: minutes, ss: seconds) -: Separator |
| 13 | 197-236 | A40 | Scene location ID (without zero suppression) ='FRAMEbCENTRE: b ~ b': SLC |

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|-------------|
| 14 | 237-360 | A124 | Blank |

Table 1.1-8 Leader File Descriptor Record

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|--|
| 1 | 1-4 | B4 | Record Number = 1 |
| 2 | 5 | B1 | First subtype code = 11 |
| 3 | 6 | B1 | Record type code = 192 |
| 4 | 7 | B1 | Second subtype code = 18 |
| 5 | 8 | B1 | Third subtype code= 18 |
| 6 | 9-12 | B4 | Record length = 720 |
| 7 | 13-14 | A2 | ASCII/EBCDIC flag = 'Ab': ASCII |
| 8 | 15-16 | A2 | Continue flag = 'bb' |
| 9 | 17-28 | A12 | Format control document ID='CEOS-SARbbbb' |
| 10 | 29-30 | A2 | Format control document revision level ='bA' |
| 11 | 31-32 | A2 | Record format revision level ='bA' |
| 12 | 33-44 | A12 | Software Release & Revision Number ='NNN.NNNbbbb' |
| 13 | 45-48 | I4 | Number of files = 'bbb1' |
| 14 | 49-64 | A16 | File ID ='MMMMMMbTFFFFbbbb' MMMMM: Mission name ('STRIX') N: Mission ID (Alpha='A', Beta='B', 1='1', 2='2', ...) T: Processing level code SLC ='B' FFFF: File type Leader file ='SARL' |
| 15 | 65-68 | A4 | Record sequence and location type flag ='FSEQ' |
| 16 | 69-76 | I8 | Sequence number of location = 'bbbbbbb1' |
| 17 | 77-80 | I4 | Field length of sequence number = 'bbb4' |
| 18 | 81-84 | A4 | Record code and location type flag = 'FTYP' |
| 19 | 85-92 | I8 | Record code position ='bbbbbbb5' |
| 20 | 93-96 | I4 | Field length of record code ='bbb4' |
| 21 | 97-100 | A4 | Record length and location type flag = 'FLGT' |
| 22 | 101-108 | I8 | Location of record length ='bbbbbbb9' |
| 23 | 109-112 | I4 | Field length of record length ='bbb4' |
| 24 | 113-180 | A68 | Blank |
| 25 | 181-186 | I6 | Number of dataset summary records ='bbbbbb1' |
| 26 | 187-192 | I6 | Dataset summary record length ='bb4096' |
| 27 | 193-198 | I6 | Number of map projection data records ='bbbbbb0' |

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|---|
| 28 | 199-204 | I6 | Map projection data record length ='bbbbbb0' |
| 29 | 205-210 | I6 | Number of platform location data records ='bbbbbb1' |
| 30 | 211-216 | I6 | Platform location data record length ='bb4680' |
| 31 | 217-222 | I6 | Number of attitude data records='bbbbbb1' |
| 32 | 223-228 | I6 | Attitude data record length = 16384 |
| 33 | 229-234 | I6 | Number of radiometric data records ='bbbbbb1' |
| 34 | 235-240 | I6 | Radiometric record length ='bb9860' |
| 35 | 241-246 | I6 | Number of radiometric compensation records ='bbbbbb0' |
| 36 | 247-252 | I6 | Radiometric compensation record length ='bbbbbb0' |
| 37 | 253-258 | I6 | Number of data quality summary records='bbbbbb1' |
| 38 | 259-264 | I6 | Data quality summary record length ='bb1620' |
| 39 | 265-270 | I6 | Number of data histogram records ='bbbbbb0' |
| 40 | 271-276 | I6 | Data histogram record length ='bbbbbb0' |
| 41 | 277-282 | I6 | Number of range spectra records ='bbbbbb0' |
| 42 | 283-288 | I6 | Range spectra record length ='bbbbbb0' |
| 43 | 289-294 | I6 | Number of DEM descriptor records ='bbbbbb0' |
| 44 | 295-300 | I6 | DEM descriptor record length ='bbbbbb0' |
| 45 | 301-306 | I6 | Number of radar parameter update records ='bbbbbb0' |
| 46 | 307-312 | I6 | Radar parameter update record length ='bbbbbb0' |
| 47 | 313-318 | I6 | Number of annotation data records ='bbbbbb0' |
| 48 | 319-324 | I6 | Annotation data record length ='bbbbbb0' |
| 49 | 325-330 | I6 | Number of detail processing records = 'bbbbbb0' |
| 50 | 331-336 | I6 | Detail processing record length = 'bbbbbb0' |
| 51 | 337-342 | I6 | Number of calibration records ='bbbbbb0' |
| 52 | 343-348 | I6 | Calibration record length ='bbbbbb0' |
| 53 | 349-354 | I6 | Number of GCP records ='bbbbbb0' |
| 54 | 355-360 | I6 | GCP record length ='bbbbbb0' |
| 55 | 361-420 | A60 | Blank |
| 56 | 421-426 | I6 | Number of facility data records = 'bbbbbb1' |
| 57 | 427-432 | I6 | Facility data record length = 'bb5000' |
| 58 | 433-720 | A288 | Blank |

Table 1.1-9 Data Set Summary Records

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|-------------------|
| 1 | 1-4 | B4 | Record Number = 2 |

| Field No. | Byte No. | Type | Description |
|-----------|----------|-------|---|
| 2 | 5 | B1 | First subtype code = 18 |
| 3 | 6 | B1 | Record type code = 10 |
| 4 | 7 | B1 | Second subtype code = 18 |
| 5 | 8 | B1 | Third subtype code = 20 |
| 6 | 9-12 | B1 | Record length = 4096 |
| 7 | 13-16 | I4 | Dataset summary record sequence number = 'bbb1' |
| 8 | 17-20 | I4 | SAR channel ID = blank |
| 9 | 21-52 | A32 | Scene ID = 'AAAAAA-YYYYMMDDThhmmssZb ~ b' AAAAAA: Satellite type (= 'STRIXN') N: A, B, 1, 2, ... YYYYMMDD: Scene center observation date (YYYY: year, MM: month, DD: day) hhmmss: Scene center observation time (hh: hour, mm: minutes, ss: seconds) -: Separator |
| 10 | 53-68 | A16 | Number of scene reference = 'bbbbbbbbbbbbbbbb' |
| 11 | 69-100 | A32 | Scene center time = 'YYYYMMDDHHMMSSTTTbbbbbbbbbbbbbb' (No zero suppression) YYYYMMDD: YYYY: year, MM: month, DD: day HHMMSSTTT: Time (UTC) |
| 12 | 101-116 | A16 | Blank |
| 13 | 117-132 | F16.7 | Geodetic latitude (degrees) in the center of the processed scene = blank: SLC |
| 14 | 133-148 | F16.7 | Geodetic longitude (degrees) in the center of the processed scene = blank: SLC |
| 15 | 149-164 | F16.7 | Processed scene center true heading (degrees) = blank: SLC |
| 16 | 165-180 | A16 | Ellipsoidal model = 'WGS84b ~ b' |
| 17 | 181-196 | F16.7 | Semi-major axis of ellipsoid (km) = 6378.1370000 |
| 18 | 197-212 | F16.7 | Semi-minor axis of ellipsoid (km) = 6356.7523142 |
| 19 | 213-228 | F16.7 | Earth mass (10^{24} kg) = 5.9740000 |
| 20 | 229-244 | F16.7 | Gravitational constant (10^{-14} m ³ / s ² kg) = 3.9860050 |
| 21 | 245-260 | F16.7 | Ellipsoid J2 parameter = 0.1082629×10^{-2} |
| 22 | 261-276 | F16.7 | Ellipsoid J3 parameter = $-0.0000254 \times 10^{-1}$ |
| 23 | 277-292 | F16.7 | Oblong parameter (mechanical shape coefficient J4 term) (10^{-1}) = $-0.0000162 \times 10^{-1}$ |
| 24 | 293-308 | A16 | Blank |
| 25 | 309-324 | F16.7 | reference height above the ellipsoid |
| 26 | 325-332 | I8 | Scene center line No. (Including zero fill) N/2 (N: number of lines) |
| 27 | 333-340 | I8 | Scene center pixel No. (Including zero fill) M/2 (M: number of pixels) |
| 28 | 341-356 | F16.7 | Processing scene length (km) = blank |

| Field No. | Byte No. | Type | Description |
|-----------|----------|-------|---|
| 29 | 357-372 | F16.7 | Processing scene width (km) = blank |
| 30 | 373-388 | A16 | Blank |
| 31 | 389-392 | I4 | Number of SAR channels ='bbb1 |
| 32 | 393-396 | A4 | Blank |
| 33 | 397-412 | A16 | Sensor platform name (ID) StriX: 'STRIXbbbbbbbbbbb' |
| 34 | 413-444 | A32 | Sensor ID and operation mode ='AAAAAA-BB-CCbb-bbbbbbbbbbbbbbbbbb' AAAAAA: Satellite type (= 'STRIXN') N:A, B, 1, 2, ... BB: SAR band ('Xb') CC: Operation mode '01': Stripmap mode '02': Sliding spotlight mode '03': Staring spotlight mode |
| 35 | 445-452 | I8 | Total satellite orbit number |
| 36 | 453-460 | F8.3 | Sensor platform geodetic latitude at nadir corresponding to scene center = blank: SLC |
| 37 | 461-468 | F8.3 | Sensor platform geodetic longitude at nadir corresponding to scene center = blank: SLC |
| 38 | 469-476 | F8.3 | Sensor platform heading at nadir corresponding to scene center = blank: SLC |
| 39 | 477-484 | F8.3 | Sensor angle (degrees) relative to the flight direction of the sensor platform = 'bb90.000' (-90.0: left side), (90.0: right side) |
| 40 | 485-492 | F8.3 | Incidence angle (degrees) at the scene center |
| 41 | 493-500 | A8 | Blank |
| 42 | 501-516 | F16.7 | Radar wavelength (m): Nominal value |
| 43 | 517-518 | A2 | Motion compensation indicator = '00' fixed = '00': no compensation = '01': on board compensation = '10': in processor compensation = '11': both on board and in processor |
| 44 | 519-534 | A16 | Range pulse code ='LINEARbFMbCHIRPb' |
| 45 | 535-550 | E16.7 | Range pulse amplitude coefficient #1 = Nominal Value Center frequency ξ_1 with respect to pulse width τ of linear FM modulation chirp (Constant term) |
| 46 | 551-566 | E16.7 | Range pulse amplitude coefficient #2 = Nominal value FM rate ξ_2 for pulse width τ of linear FM modulation chirp (Linear coefficient term) |
| 47 | 567-582 | E16.7 | Range pulse amplitude coefficient #3 = Nominal value (= 0.0) FM rate ξ_3 for pulse width τ of linear FM modulation chirp (Quadratic coefficient terms) |
| 48 | 583-598 | E16.7 | Range pulse amplitude coefficient #4 = Nominal value (= 0.0) FM rate ξ_4 for pulse width τ of linear FM modulation chirp (Cubic coefficient terms) |

| Field No. | Byte No. | Type | Description |
|-----------|----------|-------|---|
| 49 | 599-614 | E16.7 | Range pulse amplitude coefficient #5 = Nominal value (= 0.0) FM rate ξ for pulse width τ of linear FM modulation chirp (Quartic term coefficient) |
| 50 | 615-630 | E16.7 | Range pulse phase coefficient #1 (constant term) = blank |
| 51 | 631-646 | E16.7 | Range pulse phase coefficient #2 (linear coefficient term) = blank |
| 52 | 647-662 | E16.7 | Range pulse phase coefficient #3 (secondary coefficient term) = blank |
| 53 | 663-678 | E16.7 | Range pulse phase coefficient #4 (third-order coefficient term) = blank |
| 54 | 679-694 | E16.7 | Range pulse phase coefficient #5 (quartic coefficient term) = blank |
| 55 | 695-702 | I8 | Down linked data chirp extraction index linear-up chirp = 'bbbbbbb0' linear-down chirp = 'bbbbbbb1' linear-up and -down chirp = 'bbbbbbb2' |
| 56 | 703-710 | A8 | Blank |
| 57 | 711-726 | F16.7 | Sampling frequency (MHz) nominal value Set the observation auxiliary data value of the first record |
| 58 | 727-742 | F16.7 | Range gate (rise at the start of the image) (μ sec) Set the observation auxiliary data value of the first record |
| 59 | 743-758 | F16.7 | Range pulse width (μ sec) Set the observation auxiliary data value of the first record |
| 60 | 759-762 | A4 | Baseband conversion flag = 'YESb' (fixed) |
| 61 | 763-766 | A4 | Range compression flag = 'YESb': |
| 62 | 767-782 | F16.7 | Receiver gain for like polarized (at the start of the image) Nominal value |
| 63 | 783-798 | F16.7 | Receiver gain for cross-polarized (at the start of the image) Nominal value |
| 64 | 799-806 | I8 | Quantization in bits per channel = 'bbbbbbb' |
| 65 | 807-818 | A12 | Quantization descriptor = 'UNIFORMbI, Qb' |
| 66 | 819-834 | F16.7 | DC bias nominal value of component I |
| 67 | 835-850 | F16.7 | DC bias nominal value of Q component |
| 68 | 851-866 | F16.7 | Gain imbalance for I & Q = Nominal value |
| 69 | 867-882 | A16 | Blank |
| 70 | 883-898 | A16 | Blank |
| 71 | 899-914 | F16.7 | Electronic boresight |
| 72 | 915-930 | F16.7 | Mechanical boresight |
| 73 | 931-934 | A4 | Echo tracker-on/off = 'OFFb' (fixed value) |
| 74 | 935-950 | F16.7 | Acquisition PRF (mHz) |
| 75 | 951-966 | F16.7 | Two-way antenna beam width [deg] (Elevation, Effective value) = Nominal value |
| 76 | 967-982 | F16.7 | Two-way antenna beam width [deg] (Azimuth, Effective value) = Nominal value |
| 77 | 983-998 | I16 | Satellite encoded binary time code: Standard satellite time counter of error time information = blank |

| Field No. | Byte No. | Type | Description |
|-----------|-----------|-------|--|
| 78 | 999-1030 | A32 | Satellite clock time: Standard ground time of error time information (Tgref) = blank |
| 79 | 1031-1046 | I16 | Satellite clock increment [nsec]: Error time information of calculation satellitecounter cycle (Psc) = blank |
| 80 | 1047-1062 | A16 | Processing equipment (ID) = 'SYNSbbbbbbbbbbb' |
| 81 | 1063-1070 | A8 | Processing system name (ID) = 'SYNSbbbb' |
| 82 | 1071-1078 | A8 | Processing version ID Same as the first 8 characters of the volume descriptor software release & revision number |
| 83 | 1079-1094 | A16 | Process code of processing equipment = 'bbbbbbbbbbbbbbb' |
| 84 | 1095-1110 | A16 | Product level code = 'SLCbbbbbbbbbbb' (SLC) |
| 85 | 1111-1142 | A32 | Product type specifier For SLC: ='BASICbIMAGEbb ~ b' |
| 86 | 1143-1174 | A32 | Processing algorithm ID = blank |
| 87 | 1175-1190 | F16.7 | Number of looks in the azimuth direction (nominal value) SLC = 1.0 |
| 88 | 1191-1206 | F16.7 | Number of looks in the range direction (nominal value) = 1.0 |
| 89 | 1207-1222 | F16.7 | Bandwidth per look in azimuth (Hz) Same as 1239-1254 bytes |
| 90 | 1223-1238 | F16.6 | Bandwidth per look in the range direction (Hz) (3dB down width of the power spectrum of the reference function for a sub aperture look) |
| 91 | 1239-1254 | F16.7 | Bandwidth in azimuth direction (Hz) (3dB down width of power spectrum of the reference function for full aperture) |
| 92 | 1255-1270 | F16.7 | Bandwidth in the range direction (kHz) |
| 93 | 1271-1302 | A32 | Window function in azimuth direction = 1: RECTANGLE |
| 94 | 1303-1334 | A32 | Window function in the range direction = 1: RECTANGLE |
| 95 | 1335-1350 | A16 | Data input source (eq. HDDT-ID, etc.) Online transmission ='ONLINEb ~ b' |
| 96 | 1351-1366 | F16.7 | Resolution in the ground range direction (nominal value) (m) = blank: For SLC |
| 97 | 1367-1382 | F16.7 | Resolution in azimuth direction (nominal value) (m) = blank: For SLC |
| 98 | 1383-1398 | F16.7 | Radiometric parameter (Bias) = blank |
| 99 | 1399-1414 | F16.7 | Radiometric parameter (Gain) = blank |
| 100 | 1415-1430 | F16.7 | Along track Doppler frequency (center) constant term at early edge of image (Hz) |
| 101 | 1431-1446 | F16.7 | Along track Doppler frequency (center) linear coefficient terms at early edge of image (Hz / pixel) |
| 102 | 1447-1462 | F16.7 | Along track Doppler frequency (center) quadratic coefficient terms at early edge of image (Hz / pixel / pixel) |

| Field No. | Byte No. | Type | Description |
|-----------|-----------|-------|--|
| 103 | 1463-1478 | A16 | Blank |
| 104 | 1479-1494 | F16.7 | Cross track Doppler frequency (center) constant term at early edge of image (Hz) |
| 105 | 1495-1510 | F16.7 | Cross track Doppler frequency (center) linear coefficient terms at early edge of image (Hz / pixel) |
| 106 | 1511-1526 | F16.7 | Cross track Doppler frequency (center) quadratic coefficient terms at early edge of image (Hz / pixel / pixel) |
| 107 | 1527-1534 | A8 | Time direction indicator along pixel direction= blank (fixed) |
| 108 | 1535-1542 | A8 | Time direction indicator along line direction Ascending ='ASCENDbb' Descending ='DESCENDb' |
| 109 | 1543-1558 | F16.7 | Along track Doppler frequency rate constant terms at early edge of the image (Hz / sec) |
| 110 | 1559-1574 | F16.7 | Along track Doppler frequency rate linear coefficient at early edge of the image (Hz / sec / pixel) |
| 111 | 1575-1590 | F16.7 | Along track Doppler frequency rate quadratic coefficient at early edge of the imagedata (Hz / sec / pixel / pixel) |
| 112 | 1591-1606 | A16 | Blank |
| 113 | 1607-1622 | F16.7 | Cross track Doppler frequency rate constant terms at early edge of the image (Hz / sec) |
| 114 | 1623-1638 | F16.7 | Cross track Doppler frequency rate linear coefficient at early edge of the image (Hz / sec / pixel) |
| 115 | 1639-1654 | F16.7 | Cross track Doppler frequency rate quadratic coefficient at early edge of the image (Hz / sec / pixel / pixel) |
| 116 | 1655-1670 | A16 | Blank |
| 117 | 1671-1678 | A8 | Line content indicator = SLC:'RANGebbb' |
| 118 | 1679-1682 | A4 | Clutter lock applied flag ='NOTb' ='YESb','NOTb' |
| 119 | 1683-1686 | A4 | Auto-focusing applied flag ='NOTb' ='YESb','NOTb' |
| 120 | 1687-1702 | F16.7 | Line spacing (m) SLC: Calculated value of spacing in the azimuth direction |
| 121 | 1703-1718 | F16.7 | Pixel spacing (m) SLC: Calculated value of spacing in the range direction |
| 122 | 1719-1734 | A16 | Processor range compression designator = 'SYNTHETICbCHIRPb' |
| 123 | 1735-1750 | F16.7 | Doppler center frequency approximation coefficient constant term (a) |
| 124 | 1751-1766 | F16.7 | Doppler center frequency approximation coefficient Linear coefficient term (b) $fd = a + b \cdot R$ fd: Doppler center frequency (Hz) R: Slant range (km) |

| Field No. | Byte No. | Type | Description |
|------------------|-----------|--------|---|
| 125 | 1767-1770 | I4 | Calibration mode data position flag ='bbb0' No calibration mode data area ='bbb0' Observation start side ='bbb1' Observation end side ='bbb2' Observation start / end side ='bbb3' |
| 126 | 1771-1778 | I8 | Start line number of calibration at the side of start In case of calibration location flag is '0', always = 'bbbbbbb0' |
| 127 | 1779-1786 | I8 | End line number of calibration at the side of start In case of calibration location flag is '0', always = 'bbbbbbb0' |
| 128 | 1787-1794 | I8 | Start line number of calibration at the side of end In case of calibration location flag is '0', always = 'bbbbbbb0' |
| 129 | 1795-1802 | I8 | End line number of calibration at the side of end In case of calibration location flag is '0', always = 'bbbbbbb0' |
| 130 | 1803-1806 | I4 | PRF switching indicator = 'bbb0' If the PRF has not changed in one scene ='bbb0' When PRF changes in one scene ='bbb1' |
| 131 | 1807-1814 | I8 | Line number of PRF switching No change point:'bbbbbbb1' |
| 132 | 1815-1830 | F16.7 | Beam center direction (degrees) at the center of the scene |
| 133 | 1831-1834 | I4 | Yaw steering flag If not yaw steering ='bbb1' If yaw steering ='bbb0' |
| 134 | 1835-1838 | I4 | Blank |
| 135 | 1839-1854 | F16.7 | Off Nadir angle (degrees) |
| 136 | 1855-1858 | A4 | Blank |
| 137 | 1859-1886 | A28 | Blank |
| 138 | 1887-1906 | E20.13 | Incidence angle constant term (a0) (see Note 1) |
| 139 | 1907-1926 | E20.13 | Incidence angle linear coefficient term (a1) (see Note 1) |
| 140 | 1927-1946 | E20.13 | Incidence angle quadratic coefficient term (a2) (see Note 1) |
| 141 | 1947-1966 | A20 | Blank |
| 142 | 1967-1986 | A20 | Blank |
| 143 | 1987-2006 | A20 | Blank |
| Image annotation | | | |
| 144 | 2007-2014 | I8 | Number of annotation points (up to 64) ='bbbbbbb0' |
| 145 | 2015-2022 | A8 | Blank |
| 146 | 2023-2030 | I8 | Line number of 1st annotation start = blank |
| 147 | 2031-2038 | I8 | Pixel number of 1st annotation start = blank |
| 148 | 2039-2054 | A16 | 1st annotation text = blank |

| Field No. | Byte No. | Type | Description |
|-----------|-----------|-----------------------|-------------------------|
| 149-337 | 2055-4070 | (18 * 2, A * 16) * 63 | 2nd to 64th annotations |
| 338 | 4071-4096 | A26 | System reserved = blank |

Notes:

1. Fields 138–140: Incidence angle is computed as $\Theta = a_0 + a_1 \cdot R + a_2 \cdot R^2$, where Θ is the incidence angle (rad) and R is the slant range (km).

Table 1.1-10 Platform Position Data Record

| Field No. | Byte No. | Type | Description |
|-----------|----------|-------|--|
| 1 | 1-4 | B4 | Record Number = 3 |
| 2 | 5 | B1 | First subtype code = 18 |
| 3 | 6 | B1 | Record type code = 30 |
| 4 | 7 | B1 | Second subtype code = 18 |
| 5 | 8 | B1 | Third subtype code = 20 |
| 6 | 9-12 | B1 | Record length = 4680 |
| 7 | 13-44 | A32 | Orbital element type Onboard orbit = '1bbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbb' Precise orbit = '2bbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbb' |
| 8 | 45-60 | F16.7 | 1st orbital element Position vector in the earth fixed coordinate system of the scene center (x) [m] |
| 9 | 61-76 | F16.7 | 2nd orbital element Position vector in the earth fixed coordinate system of the scene center (y) [m] |
| 10 | 77-92 | F16.7 | 3rd orbital element Position vector in the earth fixed coordinate system of the scene center (z) [m] |
| 11 | 93-108 | F16.7 | 4th orbital element Velocity vector in the earth fixed coordinate system of the scene center (x') [m/sec] |
| 12 | 109-124 | F16.7 | 5th orbital element Velocity vector in the earth fixed coordinate system of the scene center (y') [m/sec] |
| 13 | 125-140 | F16.7 | 6th orbital element Velocity vector in the earth fixed coordinate system of the scene center (z') [m/sec] |
| 14 | 141-144 | I4 | Number of data points variable up to 28 Example: Onboard orbit = 'bb28' Precise orbit = 'bb28' |
| 15 | 145-148 | I4 | Year of first point = 'YYYY' |
| 16 | 149-152 | I4 | Month of first point = 'bbMM' |

| Field No. | Byte No. | Type | Description |
|-----------------------------|-----------|-----------------|--|
| 17 | 153-156 | I4 | Day of first point = 'bbDD' |
| 18 | 157-160 | I4 | Day in the year of first point (Example February 2:'bb33') |
| 19 | 161-182 | E22.15 | Seconds of the first point (Example, 0:51:30.23 = 3090.23) |
| 20 | 183-204 | E22.15 | Interval time between points (seconds) = ss |
| 21 | 205-268 | A64 | Reference Coordinate System (ECI, ECR) = 'ECRbb ~ b' |
| 22 | 269-290 | E22.15 | Greenwich mean hour angle (degrees) = blank |
| 23 | 291-306 | F16.7 | Along track position error (m) = blank |
| 24 | 307-322 | F16.7 | Across track position error (m) = blank |
| 25 | 323-338 | F16.7 | Radial position error (m/sec) = blank |
| 26 | 339-354 | F16.7 | Along track velocity error (m/sec) = blank |
| 27 | 355-370 | F16.7 | Across track velocity error (m / sec) = blank |
| 28 | 371-386 | F16.7 | Radial velocity error (m / sec) = blank |
| FIRST POSITIONAL DATA POINT | | | |
| 29 | 387-452 | 3E22.15 | First data point position vector (x, y, z) (m) |
| 30 | 453-518 | 3E22.15 | First data point velocity vector (x', y', z') (m / sec) |
| | 519-4082 | 27*6*E2 2.15 | Repeat 387-518 for up to 28 points |
| 35 | 4083-4199 | A18 | Blank |
| 36 | 4101 | I1 | Leap second flag 0: None 1: Leap second present |
| 37 | 4102-4680 | A579 | Blank |

Table 1.1-11 Attitude Data Record

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|---------------------------------|
| 1 | 1-4 | B4 | Record Number = 4 |
| 2 | 5 | B1 | First record subtype code = 18 |
| 3 | 6 | B1 | Record type code = 40 |
| 4 | 7 | B1 | Second record subtype code = 18 |
| 5 | 8 | B1 | Third record subtype code = 20 |
| 6 | 9-12 | B4 | Record length = 16384 |
| 7 | 13-16 | I4 | Number of points = 'nn' |
| 8 | 17-20 | I4 | Day of the year |
| 9 | 21-28 | I8 | Milli-second of the day |
| 10 | 29-32 | I4 | Pitch data quality flag = blank |
| 11 | 33-36 | I4 | Role data quality flag = blank |

| Field No. | Byte No. | Type | Description |
|-----------|-----------------------|-------------------------------------|--|
| 12 | 37-40 | I4 | Yaw data quality flag = blank |
| 13 | 41-54 | E14.6 | Pitch [deg] |
| 14 | 55-68 | E14.6 | Roll [deg] |
| 15 | 69-82 | E14.6 | Yaw [deg] |
| 16 | 83-86 | I4 | Pitch rate quality flag = blank |
| 17 | 87-90 | I4 | Roll rate quality flag = blank |
| 18 | 91-94 | I4 | Yaw quality flag = blank |
| 19 | 95-108 | E14.6 | Pitch rate |
| 20 | 109-122 | E14.6 | Roll rate |
| 21 | 123-136 | E14.6 | Yaw rate |
| | 137-136+1 20*(n-1) | 120*(n-1)) | Repeat bytes 17-136 for the number of points (n) |
| 22 | 137+120*(n-1)-16384 | A(16384 -(136+1 20*(n-1)) | Blank |

Table 1.1-12 Radiometric Data Records

| Field No. | Byte No. | Type | Description |
|----------------------|----------|-------|---|
| 1 | 1-4 | B4 | Record Number = 5 |
| 2 | 5 | B1 | First record subtype code = 18 |
| 3 | 6 | B1 | Record type code = 50 |
| 4 | 7 | B1 | Second record subtype code = 18 |
| 5 | 8 | B1 | Third record subtype code= 20 |
| 6 | 9-12 | B1 | Record length = 9860 |
| 7 | 13-16 | I4 | Radiometric data record sequence number ='bbb1' |
| 8 | 17-20 | I4 | Number of radiometric data fields ='bbb1' |
| RADIOMETRIC DATA SET | | | |
| 9 | 21-36 | F16.7 | Calibration factor (CF) SLC: $\beta_{\text{odB}} = 10 * \log_{10} \langle I^2 + Q^2 \rangle + \text{CF}$ (see Note 1) |
| 10 | 37-9860 | A9824 | Blank |

Notes:

1. Field 9: The backscattering coefficient (beta-naught) of a pixel can be obtained by ensemble averaging (<>), i.e., the spatial averaging of pixel values around the target. I and Q in the formula are the pixel values.

Table 1.1-13 Data Quality Summary Record

| Field No. | Byte No. | Type | Description |
|-----------------------------------|----------|-------|---|
| 1 | 1-4 | B4 | Record Number = 6 |
| 2 | 5 | B1 | First record subtype code = 18 |
| 3 | 6 | B1 | Record type code = 60 |
| 4 | 7 | B1 | Second record subtype code = 18 |
| 5 | 8 | B1 | Third record subtype code = 20 |
| 6 | 9-12 | B4 | Record length = 1620 |
| 7 | 13-16 | I4 | Data quality record number = 'bbb1' |
| 8 | 17-20 | A4 | SAR channel ID = 'ABbb' A: Received polarization (V) B: Receiving antenna (S: Single beam) |
| 9 | 21-26 | A6 | Date of the last calibration update = 'YYMMDD' YY : lower 2 figures of the year MM : Month DD : Day = blank |
| 10 | 27-30 | I4 | Number of channels (up to 8) |
| ABSOLUTE RADIOMETRIC DATA QUALITY | | | |
| 11 | 31-46 | F16.7 | ISLR (nominal value) [dB] = blank |
| 12 | 47-62 | F16.7 | PSLR (nominal value) [dB] = blank |
| 13 | 63-78 | F16.7 | Azimuth ambiguity rate (AAR) (Nominal value) = blank |
| 14 | 79-94 | F16.7 | Range ambiguity rate (RAR) (Nominal value) = blank |
| 15 | 95-110 | F16.7 | Estimate of SNR [dB] = blank |
| 16 | 111-126 | F16.7 | BER (Actual value) = blank |
| 17 | 127-142 | F16.7 | Slant range resolution (Nominal value) [m] |
| 18 | 143-158 | F16.7 | Azimuth resolution (Nominal value) [m] |
| 19 | 159-174 | F16.7 | Radiometric resolution (Nominal value) [dB] = blank |
| 20 | 175-190 | F16.7 | Instantaneous dynamic range [dB] = blank |
| 21 | 191-206 | F16.7 | Nominal absolute radiometric calibration magnitude uncertainty of SAR channel indicated in bytes 17-20 [dB] = blank |
| 22 | 207-222 | F16.7 | Nominal absolute radiometric calibration phase uncertainty of SAR channel indicated in bytes 17-20 [deg] = blank |
| RELATIVE RADIOMETRIC QUALITY | | | |
| 23 | 223-238 | F16.7 | Nominal relative radiometric calibration magnitude uncertainty of SAR channel indicated in bytes 17-20 [dB] |
| 24 | 239-254 | F16.7 | Nominal relative radiometric calibration magnitude uncertainty of SAR channel indicated in bytes 17-20 [dB] |

| Field No. | Byte No. | Type | Description |
|---------------------------------|---------------------------|-------------------------|--|
| 25 | 255 – (n-1)*32+25 4 | (n-1)*2F 16.7 | Repetition of bytes 223 - 254 for the remaining channels (up to 8 channels) |
| 26 | (n-1)*32+25 5 - 734 | A(480 -(n-1)*3 2) | Blank |
| ABSOLUTE GEOMETRIC DATA QUALITY | | | |
| 27 | 735-750 | F16.7 | Absolute location error along track (Nominal value) [m] = blank |
| 28 | 751-766 | F16.7 | Absolute location error cross track (Nominal value) [m] = blank |
| 29 | 767-782 | F16.7 | Geometric distortion scale in line direction (Nominal value) = blank |
| 30 | 783-798 | F16.7 | Geometric distortion scale in pixel direction (Nominal value) = blank |
| 31 | 799-814 | F16.7 | Geometric distortion skew = blank |
| 32 | 815-830 | F16.7 | Scene orientation error = blank |
| RELATIVE GEOMETRIC DATA QUALITY | | | |
| 33 | 831-846 | F16.7 | Along track relative misregistration error of other channels versus SAR channel (bytes 17-20) [meters] = blank |
| 34 | 847-862 | F16.7 | Cross track relative misregistration error of other channels versus SAR channel (bytes 17-20) [meters] = blank |
| 35 | 863-1086 | (n-1)*2F 16.7 | Repetition of bytes 831 - 862 for the other channels (up to 8 channels) = blank |
| 36 | 1087-1620 | A532 | Blank |

Table 1.1-14 Facility Related Data Record

| Field No. | Byte No. | Type | Description |
|-----------|----------|--------------|--|
| 1 | 1-4 | B4 | Record Number = 7 |
| 2 | 5 | B1 | First record subtype code = 18 |
| 3 | 6 | B1 | Record type code = 200 |
| 4 | 7 | B1 | Second record subtype code = 18 |
| 5 | 8 | B1 | Third record subtype code = 18 |
| 6 | 9-12 | B1 | Record length = 5000 |
| 7 | 13-16 | A4 | Blank |
| 8 | 17-416 | 20E20.1 0 | Twenty coefficients to convert from latitude and longitude to line(L) and pixel (P) position in the image. For SLC: blank |
| 9 | 417-420 | A4 | Blank |
| 10 | 421-428 | A8 | Blank |
| 11 | 429-436 | A8 | Blank |
| 12 | 437-444 | A8 | Blank |

| Field No. | Byte No. | Type | Description |
|-----------|-----------|--------------|---|
| 13 | 445-452 | A8 | Blank |
| 14 | 453-456 | I4 | PRF switching flag No change in a scene = 'bbb0' (fixed value) |
| 15 | 457-464 | I8 | Start line number of PRF switching No change = 'bbbbbbb1' (fixed value) |
| 16 | 465-472 | A8 | Blank |
| 17 | 473-480 | A8 | Blank |
| 18 | 481-488 | A8 | Blank |
| 19 | 489-800 | A312 | Blank |
| 20 | 801-1024 | A224 | Blank |
| 21 | 1025-2024 | 50E20.1 0 | Coefficients of the 8th polynomial expression to convert from pixel (P) and line (L) to latitude (φ) and longitude (λ) (see Note 1) |
| 22 | 2025-2044 | E20.10 | Origin pixel (P_0), 0.0 fixed (see Note 1) |
| 23 | 2045-2064 | E20.10 | Origin Line (L_0), 0.0 fixed (see Note 1) |
| 24 | 2065-3064 | 50E20.1 0 | Coefficients of the 8th polynomial expression to convert from latitude (Φ) and longitude (Λ) to pixel (p) and line (l) (see Note 2) |
| 25 | 3065-3084 | E20.10 | Origin Latitude (Φ_0) scene center latitude (see Note 2) |
| 26 | 3085-3104 | E20.10 | Origin Longitude (Λ_0) scene center longitude (see Note 2) |
| 27 | 3105-5000 | A1896 | Blank |

Notes:

- Field21: $\varphi = a_0 * L^4 * P^4 + a_1 * L^3 * P^4 + a_2 * L^2 * P^4 + a_3 * L * P^4 + a_4 * P^4 + a_5 * L^4 * P^3 + a_6 * L^3 * P^3 + a_7 * L^2 * P^3 + a_8 * L * P^3 + a_9 * P^3 + a_{10} * L^4 * P^2 + a_{11} * L^3 * P^2 + a_{12} * L^2 * P^2 + a_{13} * L * P^2 + a_{14} * P^2 + a_{15} * L^4 * P + a_{16} * L^3 * P + a_{17} * L^2 * P + a_{18} * L * P + a_{19} * P + a_{20} * L^4 + a_{21} * L^3 + a_{22} * L^2 + a_{23} * L + a_{24}$
 $\lambda = b_0 * L^4 * P^4 + b_1 * L^3 * P^4 + b_2 * L^2 * P^4 + b_3 * L * P^4 + b_4 * P^4 + b_5 * L^4 * P^3 + b_6 * L^3 * P^3 + b_7 * L^2 * P^3 + b_8 * L * P^3 + b_9 * P^3 + b_{10} * L^4 * P^2 + b_{11} * L^3 * P^2 + b_{12} * L^2 * P^2 + b_{13} * L * P^2 + b_{14} * P^2 + b_{15} * L^4 * P + b_{16} * L^3 * P + b_{17} * L^2 * P + b_{18} * L * P + b_{19} * P + b_{20} * L^4 + b_{21} * L^3 + b_{22} * L^2 + b_{23} * L + b_{24}$
(The order of storing: $a_0, a_1, a_2, \dots, a_{24}$ & $b_0, b_1, b_2, \dots, b_{24}$)

Fields 21–23: (P, L) in the polynomial expression are substituted as $P = p - P_0$, $L = l - L_0$, where (p, l) is an arbitrary coordinate address on the image. The position (p, l) = (0, 0) corresponds to the central point of the pixel at the upper left corner. (φ, λ) is measured in degrees.

- Field24: $p = c_0 * \Lambda^4 * \Phi^4 + c_1 * \Lambda^3 * \Phi^4 + c_2 * \Lambda^2 * \Phi^4 + c_3 * \Lambda * \Phi^4 + c_4 * \Phi^4 + c_5 * \Lambda^4 * \Phi^3 + c_6 * \Lambda^3 * \Phi^3 + c_7 * \Lambda^2 * \Phi^3 + c_8 * \Lambda * \Phi^3 + c_9 * \Phi^3 + c_{10} * \Lambda^4 * \Phi^2 + c_{11} * \Lambda^3 * \Phi^2 + c_{12} * \Lambda^2 * \Phi^2 + c_{13} * \Lambda * \Phi^2 + c_{14} * \Phi^2 + c_{15} * \Lambda^4 * \Phi + c_{16} * \Lambda^3 * \Phi + c_{17} * \Lambda^2 * \Phi + c_{18} * \Lambda * \Phi + c_{19} * \Phi + c_{20} * \Lambda^4 + c_{21} * \Lambda^3 + c_{22} * \Lambda^2 + c_{23} * \Lambda + c_{24}$
 $l = d_0 * \Lambda^4 * \Phi^4 + d_1 * \Lambda^3 * \Phi^4 + d_2 * \Lambda^2 * \Phi^4 + d_3 * \Lambda * \Phi^4 + d_4 * \Phi^4 + d_5 * \Lambda^4 * \Phi^3 + d_6 * \Lambda^3 * \Phi^3 + d_7 * \Lambda^2 * \Phi^3 + d_8 * \Lambda * \Phi^3 + d_9 * \Phi^3 + d_{10} * \Lambda^4 * \Phi^2 + d_{11} * \Lambda^3 * \Phi^2 + d_{12} * \Lambda^2 * \Phi^2 + d_{13} * \Lambda * \Phi^2 + d_{14} * \Phi^2 + d_{15} * \Lambda^4 * \Phi + d_{16} * \Lambda^3 * \Phi + d_{17} * \Lambda^2 * \Phi + d_{18} * \Lambda * \Phi + d_{19} * \Phi + d_{20} * \Lambda^4 + d_{21} * \Lambda^3 + d_{22} * \Lambda^2 + d_{23} * \Lambda + d_{24}$
(The order of storing: $c_0, c_1, c_2, \dots, c_{24}$ & $d_0, d_1, d_2, \dots, d_{24}$)

Fields 24–26: (Φ, Λ) in the polynomial expression are substituted as $\Phi = \varphi - \Phi_0$ (degrees), $\Lambda = \lambda - \Lambda_0$ (degrees), where (φ, λ) is an arbitrary position on the image. The position (p, l) = (0, 0) corresponds to the central point of the pixel at the upper left corner.

Table 1.1-15 Image File Descriptor Record

| Field No. | Byte No. | Type | Description |
|-------------------|----------|------|--|
| 1 | 1-4 | B4 | Record Number = 1 |
| 2 | 5 | B1 | First subtype code = 50 |
| 3 | 6 | B1 | Record type code = 192 |
| 4 | 7 | B1 | Second subtype code = 18 |
| 5 | 8 | B1 | Third subtype code = 18 |
| 6 | 9-12 | B4 | Record length = 720 |
| 7 | 13-14 | A2 | ASCII/EBCDIC flag = 'Ab' In case of ASCII |
| 8 | 15-16 | A2 | Blank |
| 9 | 17-28 | A12 | Format Manual ID = 'CEOS-SARbbbb' |
| 10 | 29-30 | A2 | Format Manual Management Revision Number = 'bA' |
| 11 | 31-32 | A2 | Record format revision level = 'bA' |
| 12 | 33-44 | A12 | Software Release & Revision Number = 'NNN.NNNbbbb' 001.000, 001.001, ... 002.000 |
| 13 | 45-48 | I4 | File number = 'bbb1' |
| 14 | 49-64 | A16 | File ID = 'MMMMMnTFFFFbbb' MMMMM: Mission name ('STRIX') N: Mission ID (Alpha='A', Beta='B', 1='1', 2='2', ...) T: Processing level code SLC = 'B' FFFF: File type Image file = 'IMOP' |
| 15 | 65-68 | A4 | Record sequence and location type flag = 'FSEQ' |
| 16 | 69-76 | I8 | Sequence number of location = 'bbbbbbb1' |
| 17 | 77-80 | I4 | Field length of sequence number = 'bbb4' |
| 18 | 81-84 | A4 | Record code and location type flag = 'FTYP' |
| 19 | 85-92 | I8 | Record code position = 'bbbbbbb5' |
| 20 | 93-96 | I4 | Record code field length = 'bbb4' |
| 21 | 97-100 | A4 | Record length and position format flag = 'FLGT' |
| 22 | 101-108 | I8 | Record length position = 'bbbbbbb9' |
| 23 | 109-112 | I4 | Record length bytes = 'bbb4' |
| 24 | 113-180 | A68 | Blank |
| 25 | 181-186 | I6 | Number of SAR data records = 1056 Number of signal data records |
| 26 | 187-192 | I6 | Data set summary record length |
| 27 | 193-216 | A24 | Blank |
| SAMPLE GROUP DATA | | | |
| 28 | 217-220 | I4 | Bit length per sample = 'bb32': SLC |

| Field No. | Byte No. | Type | Description |
|--------------------------------|----------|------|--|
| 29 | 221-224 | I4 | Number of samples per data group = 'bbb2': SLC |
| 30 | 225-228 | I4 | Number of bytes per data group='bbb8': SLC |
| 31 | 229-232 | A4 | Justification and order of samples within data group = blank (fixed value) |
| SAR RELATED DATA IN THE RECORD | | | |
| 32 | 233-236 | I4 | Number of SAR channels ='bbb1' |
| 33 | 237-244 | I8 | Number of lines per data set (one channel) (Excluding border lines) |
| 34 | 245-248 | I4 | Number of left border pixels per line = 'bbb0' |
| 35 | 249-256 | I8 | Number of data group (or pixels) per line (see Note 1) |
| 36 | 257-260 | I4 | Number of right border pixels per line = 'bbb0' |
| 37 | 261-264 | I4 | Number of top border lines = 'bbb0' |
| 38 | 265-268 | I4 | Number of bottom border lines = 'bbb0' |
| 39 | 269-272 | A4 | Interleaving ID = 'BSQb' (fixed value) |
| RECORD DATA IN THE FILE | | | |
| 40 | 273-274 | I2 | Number of physical records per line = 'b1' (fixed value) |
| 41 | 275-276 | I2 | Number of physical records per multi-channel line in this file = 'b1' (fixed value) |
| 42 | 277-280 | I4 | Number of bytes of PREFIX DATA per record SLC = '1056' |
| 43 | 281-288 | I8 | Number of bytes of SAR data per record (zero suppression) (see Note 1) |
| 44 | 289-292 | I4 | Number of bytes of suffix data per record = 'bbb0' (fixed value) |
| 45 | 293-296 | I4 | Prefix/suffix repeat flag = 'bbbb' (fixed value) |
| PREFIX / SUFFIX DATA LOCATORS | | | |
| 46 | 297-304 | A8 | Sample data line number locator = 'bb13b4PB' 'P': Prefix, 'S': Suffix 'A': ASCII, 'B': Binary, 'N': Numeric |
| 47 | 305-312 | A8 | SAR channel number locator = 'bb49b2PB' |
| 48 | 313-320 | A8 | Time of SAR data line locator = 'bb45b4PB' |
| 49 | 321-328 | A8 | Left-fill count locator = 'bb21b4PB' |
| 50 | 329-336 | A8 | Right-fill count locator = 'bb29b4PB' |
| 51 | 337-340 | A4 | Pad pixels present indicator = 'bbbb' |
| 52 | 341-368 | A28 | Blank |
| 53 | 369-376 | A8 | SAR data line quality code locator = 'bb97b4PB' |
| 54 | 377-384 | A8 | Calibration information field locator = 'bbbbbbbb' |
| 55 | 385-392 | A8 | Gain values field locator = 'bbbbbbbb' |
| 56 | 393-400 | A8 | Bias values filed locator = 'bbbbbbbb' |
| 57 | 401-428 | A28 | SAR data format type indicator ='COMPLEX * 8bbbbbbbbbbbbbbbb': SLC |

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|---|
| 58 | 429-432 | A4 | SAR data format type code ='C * 8b': SLC 'COMPLEX * 8bbbbbbbbbbbbbbbb'"'C * 8b'(8 byte wide) -The first half (4 bytes) in the 8-byte field is two's complement representation Including real number components in floating point format A complex representation in which the second half contains an imaginary component. |
| 59 | 433-436 | I4 | Pixel left justified bits ='bbb0' |
| 60 | 437-440 | I4 | Pixel right-justified bits ='bbb0' |
| 61 | 441-448 | I8 | Maximum pixel value (starting from 0) (zero suppression)= blank: SLC |
| 62 | 449-452 | A4 | Blank |
| 63 | 453-456 | A4 | Blank |
| 64 | 457-460 | A4 | Blank |
| 65 | 461-720 | A260 | Blank |

Notes:

1. Fields 35, 43: For SLC products, each data record corresponds to one image range line. Each range line begins at the nearest-range pixel and ends at the farthest-range pixel.

Table 1.1-16 Signal Data Records

| Field No. | Byte No. | Type | Description |
|---------------------------------|----------|------|--|
| 1 | 1-4 | B4 | Record Number = 2,3,.. |
| 2 | 5 | B1 | First record subtype code = 50 |
| 3 | 6 | B1 | Record type code = 10 |
| 4 | 7 | B1 | Second record subtype code = 18 |
| 5 | 8 | B1 | Third record subtype code= 20 |
| 6 | 9-12 | B4 | Record length |
| PREFIX DATA-GENERAL INFORMATION | | | |
| 7 | 13-16 | B4 | SAR image data line number = 1, 2, 3 ... |
| 8 | 17-20 | B4 | SAR image data record index = 1 (fixed value) (indicates the record sequence number in the image line) |
| 9 | 21-24 | B4 | Actual count of left-fill pixels = 0 (fixed value) |
| 10 | 25-28 | B4 | Actual count of data pixels (see Note 1) |
| 11 | 29-32 | B4 | Actual count of right-fill pixels = 0 |
| PREFIX DATA-SENSOR PARAMETERS | | | |
| 12 | 33-36 | B4 | Sensor parameters update flag = 0 |
| 13 | 37-40 | B4 | Sensor acquisition year Scene start line year |

| Field No. | Byte No. | Type | Description |
|--|----------|------|---|
| 14 | 41-44 | B4 | Sensor acquisition day of year Scene start line day of year |
| 15 | 45-48 | B4 | Sensor acquisition milli-seconds of day |
| 16 | 49-50 | B2 | SAR channel ID Single polarization = 1 |
| 17 | 51-52 | B2 | SAR channel code = 3 L = 0, S = 1, C = 2, X = 3, KU = 4, KA = 5 |
| 18 | 53-54 | B2 | Transmit pulse polarization (0 = H, 1 = V) |
| 19 | 55-56 | B2 | Received pulse polarization (0 = H, 1 = V) |
| 20 | 57-60 | B4 | Processing PRF [mHz] |
| 21 | 61-64 | B4 | 0 (fixed) |
| 22 | 65-66 | B2 | Onboard range compressed flag = 0 NO = 0, YES = 1 |
| 23 | 67-68 | B2 | Chirp type designator LINEAR FM CHIRP = 0 PHASE MODULATORS = 1 |
| 24 | 69-72 | B4 | Chirp length (pulse width) [nsec] |
| 25 | 73-76 | B4 | Chirp constant coefficient [Hz] = Nominal value |
| 26 | 77-80 | B4 | Chirp linear coefficient [Hz/μsec] = Nominal value |
| 27 | 81-84 | B4 | Chirp quadratic coefficient [Hz/μsec ²] = Nominal value |
| 28 | 85-92 | B8 | Sensor acquisition micro-seconds of day |
| 29 | 93-96 | B4 | Receiver gain [dB] = Nominal value |
| 30 | 97-100 | B4 | Invalid line flag NO. (Effective line) = 0 YES (Loss line) = 1 |
| 31 | 101-104 | B4 | Electronic elevation angle at nadir of antenna [deg] |
| 32 | 105-108 | B4 | Mechanical elevation angle at nadir of antenna [deg] |
| 33 | 109-112 | B4 | Electronic antenna squint angle [deg] |
| 34 | 113-116 | B4 | Mechanical antenna squint angle [deg] |
| 35 | 117-120 | B4 | Slant range to 1st data sample [m] |
| 36 | 121-124 | B4 | Data record window position (SAMPLE DELAY [nsec]) |
| 37 | 125-128 | B4 | Blank |
| PREFIX DATA-PLATFORM REFERENCE INFORMATION | | | |
| 38 | 129-132 | B4 | Platform position parameters update flag = 0 (fixed) Repeat = 0 Update = 1 |
| 39 | 133-136 | B4 | Platform latitude [1/1,000,000 deg] = 0 |
| 40 | 137-140 | B4 | Platform longitude [1/1,000,000 deg] = 0 |
| 41 | 141-144 | B4 | Platform altitude [m] = 0 |
| 42 | 145-148 | B4 | Platform ground speed [cm/sec] = 0 |

| Field No. | Byte No. | Type | Description |
|---|----------|------|--|
| 43 | 148-160 | 3B4 | Platform velocity X', Y', Z'[cm/sec] = 0 |
| 44 | 161-172 | 3B4 | Platform acceleration X'', Y'', Z''[cm/sec ²] = 0 |
| 45 | 173-176 | B4 | Platform track angle [1/1,000,000 deg] = 0 |
| 46 | 177-180 | B4 | Platform true track angle [1/1,000,000 deg] = 0 |
| 47 | 181-184 | B4 | Platform pitch angle [1/1,000,000 deg] = 0 |
| 48 | 185-188 | B4 | Platform roll angle [1/1,000,000 deg] = 0 |
| 49 | 189-192 | B4 | Platform yaw angle [1/1,000,000 deg] = 0 |
| PREFIX DATA-SENSOR/FACILITY SPECIFIC AUXILIARY DATA | | | |
| 50 | 193-196 | B4 | Latitude of 1 st pixel [1/1,000,000 deg] |
| 51 | 197-200 | B4 | Latitude of center-pixel [1/1,000,000 deg] |
| 52 | 201-204 | B4 | Latitude of last pixel [1/1,000,000 deg] |
| 53 | 205-208 | B4 | Longitude of 1st pixel [1/1,000,000 deg] |
| 54 | 209-212 | B4 | Longitude of center-pixel [1/1,000,000 deg] |
| 55 | 213-216 | B4 | Longitude of last pixel [1/1,000,000 deg] |
| 56 | 217-288 | B72 | Blank |
| 57 | 289-1056 | B768 | Observation auxiliary data = 0 |
| SAR RAW SIGNAL DATA | | | |
| | 1057-i | jBk | SAR data (see Note 2) i: Number of bytes of data + 1056 j: Number of pixels in this record k: Pixel size (byte) Repeat by the number of pixels |

Notes:

1. Field 10: For SLC products, actual count of data pixels corresponds to the number of one image range line. Each range line begins at the nearest-range pixel and ends at the farthest-range pixel.

Table 1.1-17 Trailer Descriptor Record

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|---|
| 1 | 1-4 | B4 | Record Number = 1 |
| 2 | 5 | B1 | First subtype code = 63 |
| 3 | 6 | B1 | Record type code = 192 |
| 4 | 7 | B1 | Second subtype code = 18 |
| 5 | 8 | B1 | Third subtype code = 18 |
| 6 | 9-12 | B4 | Record length = 720 |
| 7 | 13-14 | A2 | ASCII/EBCDIC flag = 'Ab' In case of ASCII |
| 8 | 15-16 | A2 | Blank |

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|--|
| 9 | 17-28 | A12 | Format Manual ID = 'CEOS-SARbbbb' |
| 10 | 29-30 | A2 | Format Manual Management Revision Number = 'bA' |
| 11 | 31-32 | A2 | Record format revision level = 'bA' |
| 12 | 33-44 | A12 | Software Release & Revision Number ='NNN.NNNbbbb' 001.000, 001.001,... 002.000 |
| 13 | 45-48 | I4 | Number of files = 'bbb1' |
| 14 | 49-64 | A16 | File ID ='MMMMMNbTFFFfbbb' MMMMM: Mission name ('STRIX') N: Mission ID (Alpha='A', Beta='B', 1='1', 2='2', ...) T: Processing level code SLC ='B' FFFF: File type Trailer file ='SART' |
| 15 | 65-68 | A4 | Command software v203 is used = 'FSEQ' |
| 16 | 69-76 | I8 | Sequence number position = 'bbbbbb1' |
| 17 | 77-80 | I4 | Sequence number field length = 'bbb4' |
| 18 | 81-84 | A4 | Record code and location type flag = 'FTYP' |
| 19 | 85-92 | I8 | Record code location = 'bbbbbb5' |
| 20 | 93-96 | I4 | Record code field length = 'bbb4' |
| 21 | 97-100 | A4 | Record length and location format flag = 'FLGT' |
| 22 | 101-108 | I8 | Record length location = 'bbbbbb9' |
| 23 | 109-112 | I4 | Record length field length = 'bbb4' |
| 24 | 113-180 | A68 | Blank |
| 25 | 181-186 | I6 | Number of data set summary records = 'bbbb0' |
| 26 | 187-192 | I6 | Dataset Summary Record Length = 'bbbb0' |
| 27 | 193-198 | I6 | Number of map projection data records = 'bbbb0' |
| 28 | 199-204 | I6 | Map projection data record length = 'bbbb0' |
| 29 | 205-210 | I6 | Number of platform position data records = 'bbbb0' |
| 30 | 211-216 | I6 | Platform position data record length = 'bbbb0' |
| 31 | 217-222 | I6 | Number of attitude data records = 'bbbb0' |
| 32 | 223-228 | I6 | Attitude data record length = 'bbbb0' |
| 33 | 229-234 | I6 | Number of radiometric data records = 'bbbb0' |
| 34 | 235-240 | I6 | Radiometric data record length = 'bbbb0' |
| 35 | 241-246 | I6 | Number of radiometric compensation records = 'bbbb0' |
| 36 | 247-252 | I6 | Radiometric Compensation Record Length = 'bbbb0' |
| 37 | 253-258 | I6 | Number of data quality summary records = 'bbbb0' |
| 38 | 259-264 | I6 | Data Quality Summary Record Length = 'bbbb0' |
| 39 | 265-270 | I6 | Number of data histograms records = 'bbbb0' |

| Field No. | Byte No. | Type | Description |
|-----------|----------|------|--|
| 40 | 271-276 | I6 | Data Histogram Record Length ='bbbbbb0' |
| 41 | 277-282 | I6 | Number of range spectra records ='bbbbbb0' |
| 42 | 283-288 | I6 | Range spectrum record length ='bbbbbb0' |
| 43 | 289-294 | I6 | Number of DEM descriptor records ='bbbbbb0' |
| 44 | 295-300 | I6 | DEM Descriptor Record Length ='bbbbbb0' |
| 45 | 301-306 | I6 | Number of radar parameter update records ='bbbbbb0' |
| 46 | 307-312 | I6 | Radar parameter update record length ='bbbbbb0' |
| 47 | 313-318 | I6 | Number of annotation data records ='bbbbbb0' |
| 48 | 319-324 | I6 | Annotation data record length ='bbbbbb0' |
| 49 | 325-330 | I6 | Number of detailed processing parameter records ='bbbbbb0' |
| 50 | 331-336 | I6 | Detailed processing parameter record length ='bbbbbb0' |
| 51 | 337-342 | I6 | Number of calibration records ='bbbbbb0' |
| 52 | 343-348 | I6 | Calibration record length ='bbbbbb0' |
| 53 | 349-354 | I6 | Number of GCP records ='bbbbbb0' |
| 54 | 355-360 | I6 | GCP record length ='bbbbbb0' |
| 55 | 361-420 | A60 | Blank |
| 56 | 421-426 | I6 | Number of facility data records ='bbbbbb0' |
| 57 | 427-432 | I6 | Facility data (1) record length ='bbbbbb0' |
| 58 | 433-720 | A288 | Blank |

1.1.6 Summary Information

The summary information file shows a snapshot of meta data for an SLC CEOS product and is included in the product. The table below shows the contents of the summary information.

Table 1.1-18 Contents of Summary Information

| No. | Section | Item Name | Keyword | Value |
|-----|----------------------------|--------------------------|------------------|--|
| 1 | Ordering information (Odi) | Processed Site/Date/Time | Odi_SiteDateTime | 'PROCESS:JAPAN-SYNS-STRIXAbYYYYMMDDbHHMMSS' YYYYMMDD : Processed date (YYYY: year, MM: month, DD: day) HHMMSS : Processed time (UTC) |

| No. | Section | Item Name | Keyword | Value |
|-----|-----------------------------|--------------------------------|-----------------------------|--|
| 2 | | Scene description ID | Scs_SceneID | 'AAAAAA-YYYYMMDDThhmmssZ' AAAAAA : Satellite name (= 'STRIXN') N:A, B , 1, 2, ... YYYYMMDD: Scene center observation date (YYYY: year, MM: month, DD: day) hhmmss: Scene center observation time (hh: hour, mm: minutes, ss: seconds) -: Separator |
| 3 | Product specification (Pds) | Product ID | Pds_ProductID | 'DDEEE' DD: Observation mode SM: Stripmap mode SL: Sliding Spotlight mode ST: Staring Spotlight mode EEE: Processing level SLC: Single Look Complex |
| 4 | | Precision of orbit data | Pds_OrbitDataPrecision | 'Precise' / 'Onboard' |
| 5 | | Precision of attitude data | Pds_AttitudeDataPrecision | 'Onboard' |
| 6 | | Nominal slant range resolution | Pds_SlantRangeResolution | |
| 7 | | Nominal azimuth resolution | Pds_AzimuthResolution | |
| 8 | Image information (Img) | Date and time of scene center | Img_SceneCenterDateTime | 'YYYYMMDDbhh:mm:ss.ttt' (UT) YYYY : Year (A.D) MM : Month (01~12) DD : Day (01~31) hh : Hour (00~23) |
| 9 | | Date and time of scene start | Img_SceneStartTime | mm : Minute (00~59) ss : Second (00~60) (ss=60 is used only by a leap second) |
| 10 | | Date and time of scene end | Img_SceneEndTime | ttt : Milli-second (000~999) |
| 11 | | Off-nadir angle | Img_OffNadirAngle | NN.N [degree] (Measured) |
| 12 | Product information (Pdi) | Data size of product | Pdi_ProductDataSize | |
| 13 | | Number of files in SLC product | Pdi_CntOfSLCProductFileName | |
| 14 | | Filename of SLC product | Pdi_SLCProductFileName | nn : 01~99 |

| No. | Section | Item Name | Keyword | Value |
|-----|-------------------------|---------------------|---------------------|---|
| 15 | | Number of pixels | Pdi_NoOfPixels | |
| 16 | | Number of lines | Pdi_NoOfLines | |
| 17 | | Product format | Pdi_ProductFormat | |
| 18 | Label information (Lbi) | Satellite name | Lbi_Satellite | 'StriX-N' N: A, B, 1, 2, ... |
| 19 | | Sensor name | Lbi_Sensor | 'SAR' |
| 20 | | Processing level | Lbi_ProcessLevel | 'SLC' |
| 21 | | Processing facility | Lbi_ProcessFacility | 'SYNS' |
| 22 | | Observation date | Lbi_ObservationDate | 'YYYYMMDD' YYYYMMDD : (YYYY: year, MM: month, DD: day) |

1.1.7 Thumbnail Image

A thumbnail image is generated by transforming a processed data type to 8 bit integer and by aggregating neighboring pixels. The image format is PNG and map projection is in slant range.

1.2 SICD Product Format

Sensor Independent Complex Data (SICD) product is contained in National Imagery Transmission Format (NITF) and is presented by single file (.nitf) [2], [3], [4], [5]. The NITF file includes both image and metadata. The SICD format follows the standard, NGA.STND.0024-1_1.3.0, NGA.STND.0024-2_1.3.0 and NGA.STND.0024-3_1.3.0.

1.2.1 Product Composition

SLC SICD product includes:

- image raster data and metadata (nitf)
- thumbnail image (jpeg)
- temporal metadata file (xml)

Note: The temporal metadata file (META_*.xml) is provided for interim use only and is not intended for image analysis. Its file format specification is not included in this document.

The naming convention for SLC SICD product files is described in the table below.

Table 1.2-1 SLC SICD product file naming convention

| File Type | Number of Files | File Name | Type | Contents |
|-----------------|-----------------|--|------|--|
| Image File | 1 | IMG-<Polarization>-<Scene ID>-<Product ID>-SICD.nitf | NITF | This file stores raster image and metadata |
| Thumbnail Image | 1 | IMG-<Polarization>-<Scene ID>-<Product ID>-SICD.jpeg | JPEG | |

Where:

Scene ID = AAAAAA-YYYYMMDDThhmmssZ

AAAAAA : Satellite type

- STRIXA: StriX- α
- STRIXB: StriX- β
- STRIX1 ~ N: StriX-1 ~ N

○ Example:

- STRIX1: StriX-1
- STRIX2: StriX-2

- : Separator

YYYYMMDD: Scene center observation date (YYYY: year, MM: month, DD: day)

hhmmss: Scene center observation time* (hh: hour, mm: minutes, ss: seconds)

*precise orbit is used when available

Product ID = DDEEE

DD: Observation mode

- SM: Stripmap mode
- SL: Sliding Spotlight mode
- ST: Staring Spotlight mode

EEE: Processing level (SLC: Single Look Complex)

1.2.2 SICD XML Metadata

XML metadata of Synspective's SICD product are compliant with the table in Section 3.2 XML Metadata Parameter Lists in the SICD standard [\[2\]](#). The field for Synspective products specific implementation is listed below.

Table 1.2-2 XML Field for Synspective products specific implementation in SICD product

| Field Name | Type | Description | Example |
|------------|------|---|---------|
| ModeID | TXT | Radar imaging mode: AAB AA – Observation mode SM – Stripmap SL – Sliding Spotlight ST – Staring Spotlight B – Looking direction L – Left, R – Right | SMR |

1.2.3 NITF Metadata

NITF metadata of Synspective's SICD product are compliant with the table in Section 3.3 NITF Header Parameters in the SICD standard [\[3\]](#).

1.2.4 Thumbnail Image

A thumbnail image is generated by transforming a processed data type to 8 bit integer and by aggregating neighboring pixels. The image format is JPEG and map projection is slant range.

2. GRD and SR-GRD Product

GRD and SR-GRD products are offered with GeoTIFF + XML format

The general specification of the GRD and SR-GRD product:

- image projected to ellipsoid (WGS 84 / UTM)
- magnitude representation (DN: Digital Number)
- no phase information
- image is resampled
- mode of observation: Stripmap, Sliding Spotlight or Staring Spotlight
- single polarization: VV
- bit depth: 16 bit
- Coordinate reference system:
 - Universal Polar Stereographic Projection(UPS) :
S 90 deg. $\leq \phi < S 80$ deg or N 84 deg. $< \phi \leq N 90$ deg
 - Universal Transverse Mercator(UTM): S 80 deg. $\leq \phi \leq N 84$ deg.
 - ϕ : scene center latitude (deg.)

The specification of the SR-GRD product:

- Applied Spatially Variant Apodization (SVA) to produce Super-Resolution Ground Range Detected Images (SR-GRD)

2.1 GeoTIFF + XML Product Format

2.1.1 Product Composition

GRD product includes:

- image raster data (COG)
- metadata (xml)
- thumbnail image (jpeg)
- Quicklook raster data (COG)
- temporal metadata file (xml)

Note: The temporal metadata file(META_*.xml) is provided for interim use only and is not intended for image analysis. Its file format specification is not included in this document.

The naming convention for the product files is described in the table below.

Table 2.1-1 GRD Product File Naming Convention

| File Type | Number of Files | File Name | Type | Contents |
|-----------------|-----------------|--|-------------------------|--|
| Image File | 1 | (GRD) IMG-<Polarization>-<Scene ID>-<Product ID>.tif (SR-GRD) IMG-<Polarization>-<Scene ID>-SR-<Product ID>.tif | Cloud Optimized GeoTIFF | This file stores a raster image. The raster is calibrated. The file is tiled, but doesn't have overviews. |
| Metadata File | 1 | (GRD) PAR-<Polarization>-<Scene ID>-<Product ID>.xml (SR-GRD) PAR-<Polarization>-<Scene ID>-SR-<Product ID>.xml | xml | This file stores information about raster image and observation |
| Thumbnail Image | 1 | (GRD) IMG-<Polarization>-<Scene ID>-<Product ID>.jpeg (SR-GRD) IMG-<Polarization>-<Scene ID>-SR-<Product ID>.jpeg | JPEG | |
| Image File | 1 | (GRD) IMG-<Polarization>-<Scene ID>-<Product ID>_quicklook.tif (SR-GRD) IMG-<Polarization>-<Scene ID>-SR-<Product ID>_quicklook.tif | Cloud Optimized GeoTIFF | This file stores a raster image. This raster is not calibrated. The details are in Section 2.1.5 . |

Where:

Scene ID = AAAAAA-YYYYMMDDThhmmssZ

AAAAAA : Satellite type

- STRIXA: StriX- α
- STRIXB: StriX- β
- STRIX1 ~ N: StriX-1 ~ N

○ Example:

- STRIX1: StriX-1
- STRIX2: StriX-2

- : Separator

YYYYMMDD: Scene center observation date (YYYY: year, MM: month, DD: day)

hhmmss: Scene center observation time* (hh: hour, mm: minutes, ss: seconds)

*precise orbit is used when available

Product ID = DDEEE

DD: Observation mode

- SM: Stripmap mode
- SL: Sliding Spotlight mode
- ST: Staring Spotlight mode

EEE: Processing level (GRD: Ground Range Detected)

2.1.2 XML Metadata

The definition of data type is shown in the table below.

Table 2.1-2 GRD XML Tag and Attribute Name

| Tag / Attribute Name | Type [Unit] | Description | Example / Remarks |
|-------------------------------------|--------------|--|--|
| gml:metaDataProperty | | | |
| eop:EarthObservationMetadata | | | Nested under gml:metaDataProperty |
| eop:creationDate | date time | Creation date (ISO 8601) YYYY-MMDDThh:mm:ssZ | 2026-04-09T03:45:05Z |
| eop:acquisitionType | string | Acquisition type | NOMINAL / CALIBRATION |
| eop:acquisitionSubType | string | Acquisition mode | StaringSpotlight, SlidingSpotlight, or Stripmap |
| eop:status | string | Product status | ARCHIVED |
| eop:processing | | | Nested under eop:EarthObservationMetadata |
| eop:ProcessingInformation | | | Nested under eop:processing |
| eop:processingDate | date time | Processing date (UTC, ISO 8601) YYYY-MMDDThh:mm:ssZ | 2026-04-09T03:45:05Z |
| eop:method | string | GRD interpolation method | NN: Nearest Neighbor, BL: Bilinear |
| eop:processorName | string | Processing software name | GrdProcessor |
| eop:processorVersion | string | Software version (Major.Minor.Patch) | 2.2.2 |
| eop:processingLevel | string | Processing level | GRD |
| sar:sarProcessingParameter | | | Nested under eop:ProcessingInformation |
| sar:numberOfRangeLooks | integer | Number of looks in range direction | 1 |
| sar:numberOfAzimuthLooks | integer | Number of looks in azimuth direction | 1 |
| sar:rangePixelSpacing | double [m] | Pixel spacing in range at the scene center | 1.0 |

| Tag / Attribute Name | Type [Unit] | Description | Example / Remarks |
|--|--------------|--|---|
| sar:azimuthPixelSpacing | double [m] | Pixel spacing in azimuth at the scene center | 1.0 |
| sar:processingPRF | double [Hz] | Pulse repetition frequency used for processing | 8896.880937 |
| eop:nativeProductFormat | string | Data format | GeoTIFF |
| eop:vendorSpecific | | | Nested under eop:EarthObservationMeta Data |
| eop:SpecificInformation | | Consists of a pair of <eop:localAttribute> and <eop:localValue>. | Nested under eop:vendorSpecific |
| <eop:localAttribute> = 'offnadirAngle' | double | [Value stored in eop:localValue] Off-nadir angle | 43.32 |
| <eop:localAttribute> = 'calibrationFactor' | double | [Value stored in eop:localValue] Calibration factor (CF) to convert DN to σ_0 . $\sigma_0 = DN^2 / CF^2$. Refer to Section 4 for details. | 251.2 |
| <eop:localAttribute> = 'sceneCenterDateTime' | datetime | [Value stored in eop:localValue] Scene center time (ISO 8601). Precise orbit is used when available. | 2026-04-09T00:38:17Z |
| <eop:localAttribute> = 'neszMaximumPower' | double [dB] | [Value stored in eop:localValue] Maximum Noise Equivalent Sigma Zero value | -17.387 |
| <eop:localAttribute> = 'neszMinimumPower' | double [dB] | [Value stored in eop:localValue] Minimum Noise Equivalent Sigma Zero value | -20.755 |
| <eop:localAttribute> = 'groundRangeResolution' | double [m] | [Value stored in eop:localValue] Ground range resolution | 0.674 |
| gml:target | | | |
| eop:Footprint | | | Nested under gml:target |
| gml:posList | string [deg] | Scene footprint corners (latitude, longitude). See Note 1. | -1.896944000 42.996389000 -2.650000000 42.862778000 -2.861667000 43.381667000 -2.102500000 43.516667000 -1.896944000 42.996389000 |
| gml:pos | string [deg] | Scene center (latitude, longitude). See Note 2. | 42.88490961640794 27.6624521478024 |
| gml:using | | | |

| Tag / Attribute Name | Type [Unit] | Description | Example / Remarks |
|--------------------------------------|--------------|---|---|
| eop:EarthObservationEquipment | | | Nested under gml:using |
| eop:platform | | | Nested under eop:EarthObservationEquipment |
| eop:shortName | string | Satellite name | StriX |
| eop:serialIdentifier | string | Satellite ID | alpha, beta, 1, 2, 3 |
| eop:orbitType | string | Orbit category LEO : Low earth orbit | LEO |
| orbit | | | Nested under eop:platform |
| orbitHeader | | | Nested under orbit |
| stateVecFormat | string | Format of orbit state vectors | pos(m),vel(m/s) |
| numStateVectors | integer | Number of orbit state vector data points | 28 |
| firstStateTime | | | Nested under orbitHeader |
| firstStateTimeUTC | date time | UTC time of the first state vector | 2026-04-09T00:33:17.803476 |
| lastStateTime | | | Nested under orbitHeader |
| lastStateTimeUTC | date time | UTC time of the last state vector | 2026-04-09T00:43:17.803470 |
| stateVec | | Repeated for each data point | Nested under orbit |
| timeUTC | date time | UTC time at Nth point | 2026-04-09T00:33:17.803476 |
| posX | single [m] | Satellite position (x) in Earth-fixed coordinate system | 1.616347930072013E+06 |
| posY | single [m] | Satellite position (y) in Earth-fixed coordinate system | 3.012035692491928E+06 |
| posZ | single [m] | Satellite position (z) in Earth-fixed coordinate system | 5.983871157491785E+06 |
| velX | single [m/s] | Satellite velocity (x) in Earth-fixed coordinate system | 5.026816675713698E+03 |
| velY | single [m/s] | Satellite velocity (y) in Earth-fixed coordinate system | 4.520546614900161E+03 |
| velZ | single [m/s] | Satellite velocity (z) in Earth-fixed coordinate system | -3.623394296869903E+03 |

| Tag / Attribute Name | Type [Unit] | Description | Example / Remarks |
|-------------------------------------|--------------------|--|--|
| eop:instrument | | | Nested under eop:EarthObservationEquipment |
| eop:shortName | string | Instrument name | SAR |
| eop:sensor | | | Nested under eop:EarthObservationEquipment |
| eop:sensorType | string | Sensor type | RADAR |
| eop:operationalMode | string | Observation mode | StaringSpotlight, SlidingSpotlight, or Stripmap |
| eop:slantRangeResolution | double [m] | Nominal slant range resolution | 0.5 |
| eop:azimuthResolution | double [m] | Nominal azimuth resolution | 0.9 |
| eop:acquisitionParameters | | | Nested under eop:EarthObservationEquipment |
| sar:Acquisition | | | Nested under eop:acquisitionParameters |
| eop:orbitDirection | string | Orbit direction | ASCENDING or DESCENDING |
| sar:polarisationMode | string | Polarization mode. S: single, D: dual, Q: quad | S |
| sar:polarisationChannels | string | Polarization channels | VV |
| sar:antennaLookDirection | string | Observation direction | LEFT or RIGHT |
| sar:satelliteHeadingAngle | single [deg] | Satellite heading angle. North is 0 degrees, clockwise (0 to 360). | 189.013 |
| sar:minimumIncidenceAngle | single [deg] | Minimum incidence angle "NN.NNN" | 47.572 |
| sar:maximumIncidenceAngle | single [deg] | Maximum incidence angle "NN.NNN" | 48.199 |
| sar:incidenceAngleVariation | single [deg] | Difference between minimum and maximum incidence angle "NN.NNN" | 0.626 |
| sar:incidenceAngleConstant | single [deg] | Incidence angle polynomial constant term (see Note 3) | 8.303E-01 |
| sar:incidenceAngleLinearCoefficient | single [deg/pixel] | Incidence angle polynomial linear term (see Note 3) | 9.567E-07 |

| Tag / Attribute Name | Type [Unit] | Description | Example / Remarks |
|--|----------------------------------|--|--|
| sar:incidenceAngleQuadraticCoefficient | single [deg/pixel ²] | Incidence angle polynomial quadratic term (see Note 3) | -1.177E-12 |
| sar:acquisitionPRF | double [Hz] | Pulse repetition frequency used for data acquisition | 4480.287 |
| sar:carrierFrequency | single [Hz] | Carrier frequency | 9650000000 |
| sar:rangeSamplingFrequency | single [Hz] | Range sampling frequency | 375000000 |
| sar:chirpBandWidth | single [Hz] | Frequency chirp bandwidth | 300000000 |
| gml:resultOf | | | |
| eop:EarthObservationResult | | | Nested under gml:resultOf |
| eop:ProductInformation | | | |
| | | | Nested under eop:EarthObservationResult |
| eop:referenceSystemIdentifier | string | Projection coordinate system ID (EPSG) | epsg:32638 |
| eop:mapProjection | string | Map projection | UTM |
| eop:size | int [byte] | Raster file size | 133051382 |
| eop:numberOfPixel | int | Number of pixels | 11593 |
| eop:numberOfLine | int | Number of lines | 11072 |
| eop:imageNumberOfBits | int [bit] | Number of bits per pixel | 16 |

Notes:

1. gml:posList contains 5 coordinate pairs (latitude, longitude) forming a closed polygon (first pair = last pair). Values are separated by spaces. Corner order: left-top, left-bottom, right-bottom, right-top, left-top. Latitude is expressed as "SNN.NNNNNNNNN", longitude as "SNNN.NNNNNNNNN", where S is the sign (plus sign omitted).
2. gml:pos contains a single coordinate pair (latitude, longitude) separated by a space. Latitude is expressed as "SNN.NNNNNNNNNNNNNNN", longitude as "SNNN.NNNNNNNNNNNNNNN" (14 decimal places), where S is the sign (plus sign omitted).
3. Incidence angle is computed as: $\theta = a_0 + a_1 \cdot P + a_2 \cdot P^2$, where θ is the incidence angle (rad) and P is the pixel position. The three coefficients correspond to [sar:incidenceAngleConstant](#) (a0), [sar:incidenceAngleLinearCoefficient](#) (a1), and [sar:incidenceAngleQuadraticCoefficient](#) (a2).

2.1.3 GeoTIFF Tag

The definition of data type is shown in the table below.

Table 2.1-3 GeoTIFF Tag

| Tag / Attribute Name | Key ID | Type | Count | Description/ Example |
|-----------------------------|---------------|-------------|------------------------|---|
| ImageWidth | 256 | LONG | 1 | Number of pixels |
| ImageLength | 257 | LONG | 1 | Number of lines |
| BitsPerSample | 258 | SHORT | 1 | 16 |
| Compression | 259 | SHORT | 1 | 5: LZW (Lempel-Ziv-Welch) |
| PhotometricInterpretation | 262 | SHORT | 1 | 1 |
| SamplePerPixel | 277 | SHORT | 1 | 1 |
| PlanarConfiguration | 284 | SHORT | 1 | 1 |
| Predictor | 317 | SHORT | 1 | 1: no predictor |
| TileWidth | 322 | LONG | 1 | Tile width |
| TileLength | 323 | LONG | 1 | Tile length |
| TileOffsets | 324 | LONG | Number of tiles | Offsets to each tile |
| TileByteCounts | 325 | LONG | Number of tiles | Byte counts for each tile |
| SampleFormat | 339 | SHORT | SamplesPerPixel | 1: unsigned integer |
| GTModelTypeGeoKey | 1024 | SHORT | 1 | 1: ModelTypeProjected 2: ModelTypeGeographic 3: ModelTypeGeocentric |
| GTRasterTypeGeoKey | 1025 | SHORT | 1 | 1: RasterPixelIsArea 2: RasterPixelIsPoint |
| GTCitationGeoKey | 1026 | ASCII | 1 | WGS 84 / UTM zone 18S |
| GeogLinearUnitsGeoKey | 2052 | SHORT | 1 | 9001=Linear_Meter[m] |
| GeogAngularUnitsGeoKey | 2054 | SHORT | 1 | 9102=Angular_Degree[deg] |
| ProjectedCSTypeGeoKey | 3072 | SHORT | 1 | Projected coordinate reference system |
| ModelPixelScaleTag | 33550 | DOUBLE | 3 | Pixel spacing (meters) |
| ModelTiepointTag | 33922 | DOUBLE | 6*number of tie points | longitude and latitude of the left top corner |
| GeoKeyDirectoryTag | 34735 | SHORT | 4 | Based on GeoTIFF standards |
| GeoAsciiParamsTag | 34737 | ASCII | - | Based on GeoTIFF standards: "WGS 84 / UTM zone 18S WGS 84 " |

2.1.4 Thumbnail Image

A thumbnail image is generated by transforming a processed data type to 8 bit integer and by aggregating neighboring pixels. The image format is JPEG and map projection is in north-up orientation. The pixel value is generated with HDR tone mapping techniques.

2.1.5 Quicklook raster data (COG)

QuickLook raster file is optimized for web display with tiling, six overview levels, 8-bit conversion, and JPEG formatting. It contains two bands: the first band holds the actual data, while the second band is an alpha channel for masking not data values. Additionally, the 8bit data is generated with HDR tone mapping techniques.

3. ORT Product

The overall specifications for the ORT product are detailed below:

- input: SLC (SICD format)
- output: Cloud Optimized GeoTIFF
 - ORT sigma-naught - backscatter calibrated using the ellipsoid incidence angle
 - ORT gamma-naught - backscatter normalised by the local illuminated area using Radiometric Terrain Correction (RTC).
- Backscatter values are radiometrically calibrated and expressed in linear power scale. No additional calibration factor or scale factor needs to be applied — pixel values can be used directly for quantitative analysis.
- metadata: XML format
- image projected to DEM surface
- mode of observation:
 - Stripmap
 - Sliding Spotlight
 - Staring Spotlight
- single polarization: VV
- coordinate reference system:
 - Universal Transverse Mercator (UTM)
 - S 80 deg. $\leq \phi \leq$ N 84 deg.
- pixel spacing:
 - Stripmap: 5.0 m x 5.0 m
 - Sliding Spotlight: 1.25 m x 1.25 m
 - Staring Spotlight: 1.25 m x 1.25 m

3.1 GeoTIFF + XML Product Format

3.1.1 Product Composition

The ORT product is delivered with the following files, each provided for both sigma-naught and gamma-naught:

- backscatter image (COG)
- quicklook image (COG)
- Metadata (xml)

Additional files:

- thumbnail image (jpeg)
- local incidence angle map (GeoTIFF)
- layover/shadow mask (GeoTIFF)

The naming convention for ORT product files is described in the table below.

Table 3.1-1 ORT Product File Naming Convention

| File Type | Number of Files | File Name | Type | Contents |
|-----------------|-----------------|---|------|--|
| Image File | 1 | IMG-<Polarization>-<Scene ID> -<Product ID>-sigma0.tif | COG | sigma-naught calibrated backscatter image |
| Image File | 1 | IMG-<Polarization>-<Scene ID> -<Product ID>-gamma0.tif | COG | gamma-naught with RTC calibrated backscatter image |
| Image File | 1 | IMG-<Polarization>-<Scene ID> -<Product ID>-sigma0-quicklook.tif | COG | sigma-naught quicklook image in dB scale |
| Image File | 1 | IMG-<Polarization>-<Scene ID> -<Product ID>-gamma0-quicklook.tif | COG | gamma-naught quicklook image in dB scale |
| Thumbnail Image | 1 | IMG-<Polarization>-<Scene ID> -<Product ID>.jpeg | JPEG | gamma-naught thumbnail image in dB scale (1st-99th percentile contrast stretch). |
| Metadata File | 1 | IMG-<Polarization>-<Scene ID> -<Product ID>-sigma0-metadata.xml | XML | sigma-naught product metadata |
| Metadata File | 1 | IMG-<Polarization>-<Scene ID> -<Product ID>-gamma0-metadata.xml | XML | gamma-naught product metadata |
| Image File | 1 | IMG-<Polarization>-<Scene ID> -<Product ID>-incmap.tif | COG | incidence angle map |
| Image File | 1 | IMG-<Polarization>-<Scene ID> -<Product ID>-lsmask.tif | COG | layover and shadow classification mask |

Total: 9 files per ORT delivery.

where:

Scene ID = AAAAAA-YYYYMMDDThhmmssZ

- AAAAAA : satellite id (e.g. STRIX1)
- - : separator
- YYYYMMDD: scene center observation date
 - YYYY: year, MM: month, DD: day
- hhmmss: scene center observation time using precise orbit when available
 - hh: hour, mm: minutes, ss: seconds
- Z : time is expressed in UTC time zone

Product ID = DDEEE

- DD: Observation mode
 - SM: Stripmap mode
 - SL: Sliding Spotlight mode

- ST: Staring Spotlight mode
- EEE: Processing level (ORT: Orthorectified)

Example, for the stripmap mode, an input Single Look Complex (SLC) filename like `IMG-VV-STRIX3-20260309T154126Z-SMSLC-SICD.nitf` is transformed into an Orthorectified (ORT) output filename, such as `IMG-VV-STRIX3-20260309T154126Z-SMORT-sigma0.tif`.

3.1.2 XML Metadata

The metadata files follow the CEOS-ARD Normalised Radar Backscatter schema as defined in [6]. The Synspective ORT gamma-naught product is currently under peer review for CEOS-ARD NRB compliance. The sigma-naught and gamma-naught metadata files share the same structure but differ in a few fields (see XML Metadata Note 1). The table below describes all XML tags and attributes for the gamma-naught metadata file. In the table, XML elements are listed as tag names (e.g., `Product`, `Satellite`) and their attributes are prefixed with `@` (e.g., `@type`, `@copyright`).

Table 3.1-2 ORT XML Metadata Tag and Attribute Name

| Tag / Attribute Name | Type | Description | Example / Remarks |
|---------------------------|--------------|--|---|
| Product | | Root element | |
| @type | string | CEOS-ARD product type name | Normalised Radar Backscatter |
| @copyright | string | Copyright holder | Synspective |
| DocumentIdentifier | | Reference to CEOS-ARD PFS document | |
| @name | string | Specification name | CEOS-ARD for Synthetic Aperture Radar |
| @version | string | Specification version | 1.2 |
| (text value) | string (URL) | URL to PFS document | https://ceos.org/ard/files/PFS/SAR/v1.2/CEOS-ARD_PFS_Synthetic_Aperture_Radar_v1.2.pdf |
| DataCollectionTime | | Time range of the data collection | |
| NumberOfAcquisitions | integer | Number of source data acquisitions | 1 |
| FirstAcquisitionDate | date time | Start UTC time of data collection (ISO 8601) | 2026-04-01T15:41:21.533261Z |
| LastAcquisitionDate | date time | End UTC time of data collection (ISO 8601) | 2026-04-01T15:41:31.979895Z |
| SourceAttributes | | Source data attributes for each acquisition | Repeats per acquisition |
| @acqID | string | Sequential acquisition identifier | 1 |

| Tag / Attribute Name | Type | Description | Example / Remarks |
|--|--------------|--|---|
| SourceDataRepository | string (URL) | Location from where source data can be retrieved | https://data.synspective.io/ |
| Satellite | string | Satellite name | StriX-3 |
| Instrument | string | Instrument name | SAR |
| SatelliteReference | string (URL) | Reference URL to satellite information | https://synspective.com/satellite/satellite-strix/ |
| SourceDataAcquisitionTime | | Acquisition start and end times | Nested under SourceAttributes |
| StartTime | date time | Acquisition start time (UTC, ISO 8601) | 2026-04-01T15:41:21.533261Z |
| EndTime | date time | Acquisition end time (UTC, ISO 8601) | 2026-04-01T15:41:31.979895Z |
| SourceDataAcquisitionParameters | | SAR antenna acquisition parameters | Nested under SourceAttributes |
| RadarBand | string | Radar frequency band | X |
| RadarCenterFrequency | float [Hz] | Radar center frequency | 9.65e+09 |
| ObservationMode | string | Acquisition mode name | Stripmap, Sliding Spotlight, or Staring Spotlight |
| Polarizations | string | Polarization channel(s) | VV |
| AntennaPointing | string | Antenna look direction | Right or Left |
| BeamID | string | Beam mode mnemonic (ModeID from SICD, see Table 1.2-2) | SMR, SLL, STR, etc. |
| OrbitInformation | | Platform orbit information | Nested under SourceAttributes |
| PassDirection | string | Orbit pass direction | Ascending or Descending |
| PlatformHeading | float [deg] | Platform heading angle. North is 0 degrees; clockwise positive. Negative values indicate counter-clockwise from the North. | 193.51 (descending), -13.34 (ascending) |
| SourceProcParam | | Source data processing parameters | Nested under SourceAttributes |
| ProcessingFacility | string | Source product processing facility | Synspective/Tokyo |
| ProcessingDate | date time | Source product processing date (UTC, ISO 8601) | 2026-04-01T20:56:16.470679Z |
| SoftwareVersion | string | SLC SICD version (see Table 5-2) | 2.2.2 |
| ProductID | string | Source product filename | IMG-VV-STRIX3-20260401T154126Z-SMSLC-SICD.nitf |
| ProductLevel | string | Source product processing level | SLC |
| AzimuthNumberOfLooks | integer | Number of looks in azimuth direction | 1 |

| Tag / Attribute Name | Type | Description | Example / Remarks |
|----------------------------------|------------------|--|---|
| RangeNumberOfLooks | integer | Number of looks in range direction | 1 |
| SourceDataImageAttributes | | Source SLC image attributes | Nested under SourceAttributes |
| SourceDataGeometry | string (WKT) | Source SLC image footprint geometry in WGS84 | POLYGON ((...)) |
| AzimuthPixelSpacing | float [m] | Source SLC azimuth pixel spacing | 2.20 (SM), 0.80 (SL) |
| RangePixelSpacing | float [m] | Source SLC range pixel spacing | 1.50 (SM), 0.40 (SL) |
| AzimuthResolution | float [m] | Source SLC azimuth resolution | 2.39 (SM), 0.80 (SL) |
| RangeResolution | float [m] | Source SLC slant range resolution | 1.77 (SM), 0.44 (SL) |
| CEOS-ARDProductAttributes | | ORT product attributes and parameters | |
| DataAccess | | ORT product processing information | Nested under CEOS-ARD ProductAttributes |
| ProcessingFacility | string | ORT product processing facility | Synspective/Tokyo |
| ProcessingTime | date time | ORT product processing date (UTC, ISO 8601) | 2026-04-01T21:06:09.144751Z |
| SoftwareVersion | string | ORT processor software version (CalVer) | 2026.04 |
| Repository | string (URL) | Location from where ORT product can be retrieved | https://data.synspective.io/ |
| ProductSampleSpacing | | Output pixel spacing | Nested under CEOS-ARD ProductAttributes |
| ProductColumnSpacing | float [m] | Pixel spacing in easting (column) direction | 5.00 (SM), 1.25 (SL/ST) |
| ProductRowSpacing | float [m] | Pixel spacing in northing (row) direction | 5.00 (SM), 1.25 (SL/ST) |
| Filtering | | Speckle filter information | Nested under CEOS-ARD ProductAttributes |
| FilterApplied | string (bool) | Flag if speckle filter has been applied | False |
| ProductBoundingBox | | Bounding box corners of the product file | Two instances: UL and LR |
| @Corner | string | Corner identifier | UL or LR |
| Northing | float [m] | Northing coordinate in product CRS | 5079400.00 |
| Easting | float [m] | Easting coordinate in product CRS | 331655.00 |

| Tag / Attribute Name | Type | Description | Example / Remarks |
|-------------------------------------|-----------------|---|---|
| Latitude | float [deg] | Geodetic latitude (WGS84) | -44.419119 |
| Longitude | float [deg] | Geodetic longitude (WGS84) | 168.885325 |
| ProductGeographicalExtentUTM | | <i>SAR swath footprint</i> polygon in product CRS | Nested under CEOS-ARD ProductAttributes |
| @type | string | Geometry format | WKT |
| @order | string | Coordinate order | easting northing |
| (text value) | string (WKT) | Bounding box polygon in product map projection coordinates | POLYGON ((...)) |
| ProductGeographicalExtent | | <i>SAR swath footprint</i> polygon in geographic coordinates | Nested under CEOS-ARD ProductAttributes |
| @type | string | Geometry format | WKT |
| @order | string | Coordinate order | longitude latitude |
| (text value) | string (WKT) | Bounding box polygon in WGS84 longitude/latitude | POLYGON ((...)) |
| ProductImageSize | | Output image dimensions | Nested under CEOS-ARD ProductAttributes |
| NumberLines | integer | Number of lines (rows) in the image | 15595 |
| NumPixelsPerLine | integer | Number of pixels (columns) per line | 8354 |
| PixelCoordinate Convention | string | Pixel coordinate reference point | Pixel Centre |
| CoordinateReferenceSystem | | Map projection of the product. Provided twice: as EPSG code and as WKT. | Nested under CEOS-ARD ProductAttributes |
| @type | string | CRS representation type | EPSG or WKT |
| (text value, EPSG) | integer | EPSG code of the projected CRS | 32759 (WGS 84 / UTM zone 59S) |
| (text value, WKT) | string | Full CRS definition in WKT format | PROJCRS["WGS 84 / UTM zone 59S", ...] |
| PerPixelMetadata | | Per-pixel auxiliary data layers | Nested under CEOS-ARD ProductAttributes |
| DataMask | | Layover/shadow mask file specification | Nested under PerPixelMetadata |
| FileName | string | Mask file name | IMG-VV-STRIX3-20260401 T154126Z-SMORT-lsmap.tif |
| SampleType | string | Data layer type | Mask |
| DataFormat | string | File format | Cloud Optimized GeoTIFF |
| DataType | string | Pixel data type | Byte |

| Tag / Attribute Name | Type | Description | Example / Remarks |
|-----------------------------------|-------------|--|---|
| BitsPerSample | integer | Bits per pixel | 8 |
| BitValues | | Bit value definitions | Nested under DataMask |
| ValidData | integer | Valid data pixel value | 1 |
| Layover | integer | Layover pixel value | 5 |
| Shadow | integer | Shadow pixel value | 17 |
| Layover_shadow | integer | Combined layover and shadow pixel value | 21 |
| InvalidData | integer | Invalid data pixel value | 255 |
| NoData | integer | No data pixel value | 0 |
| LocalIncAngle | | Local incidence angle file specification | Nested under PerPixelMetadata |
| FileName | string | Incidence angle file name | IMG-VV-STRIX3-20260401T15 4126Z-SMORT-incmap.tif |
| SampleType | string | Data layer type [deg] | Angle |
| DataFormat | string | File format | Cloud Optimized GeoTIFF |
| DataType | string | Pixel data type | UINT |
| BitsPerSample | integer | Bits per pixel | 16 |
| ByteOrder | string | Byte order | Little Endian |
| ConversionEq | string | Equation to convert DN (digital number) to [deg] angle in degrees | 0.01*DN |
| BackscatterMeasurementData | | Backscatter image file specification | Nested under CEOS-ARD ProductAttributes |
| Backscatter Measurement | string | Backscatter type | gamma0 |
| Backscatter Convention | string | Backscatter value format | Linear Power |
| Backscatter ConversionEq | string | Equation to convert pixel values to dB | $10 \cdot \log_{10}(\text{DN})$ |
| Polarization | string | Polarization channel | VV |
| FileName | string | Backscatter image file name | IMG-VV-STRIX3-20260401T15 4126Z-SMORT-gamma0.tif |
| DataFormat | string | File format | Cloud Optimized GeoTIFF |
| DataType | string | Pixel data type | Float |
| BitsPerSample | integer | Bits per pixel | 32 |
| ByteOrder | string | Byte order | Little Endian |
| NoiseRemoval | | Noise removal information | Nested under CEOS-ARD ProductAttributes |

| Tag / Attribute Name | Type | Description | Example / Remarks |
|--------------------------------------|---------------|---|--|
| NoiseRemovalApplied | string (bool) | Flag if thermal noise removal has been applied | False |
| RadiometricTerrainCorrections | | RTC algorithm reference (gamma0 metadata only) | Nested under CEOS-ARD ProductAttributes |
| RTCAgorithm | string (DOI) | DOI reference to the RTC algorithm (Small, 2011 [7]) | https://doi.org/10.1109/TGRS.2011.2120616 |
| GeometricCorrections | | Geometric correction information | Nested under CEOS-ARD ProductAttributes |
| DigitalElevationModel | | DEM used for terrain correction | Nested under GeometricCorrections |
| @dem | string | DEM type | Surface |
| DEMReference | string (URL) | Reference URL to the DEM data source | https://registry.opendata.aws/copernicus-dem/ |
| DEMVersion | string | DEM version identifier | 2021_1 |
| EGMReference | string (DOI) | Reference to Earth Gravitational Model used | https://doi.org/10.1029/2011JB008916 |
| GeoCorrAccuracy | | Absolute location error (ALE) estimates | Nested under GeometricCorrections |
| @type | string | Accuracy measurement type | Orthorectified |
| @ALESource | string | ALE measurement context. "ARD" indicates end-to-end ALE measured directly in the orthorectified product. | ARD |
| NorthernSTDev | float [m] | Standard deviation of absolute location error in northing direction | 2.59 |
| EasternSTDev | float [m] | Standard deviation of absolute location error in easting direction | 2.16 |
| NorthernBias | float [m] | Bias (systematic offset) in northing direction. Positive = northward shift. | 1.52 |
| EasternBias | float [m] | Bias (systematic offset) in easting direction. Positive = eastward shift. | 0.54 |
| GriddingConvention | | Fixed grid alignment convention | Nested under GeometricCorrections |
| @type | string | Description type | Description |
| (text value) | string | Grid alignment rule. Upper left corner coordinates are aligned to exact multiples of the pixel spacing, offset by half a pixel, ensuring pixel-aligned repeat acquisitions. | Scene Upper Left Corner coordinates (Northing and Easting) are aligned to multiples of 5.00 m, offset by half a pixel. |

XML Metadata Notes:

1. Differences between sigma0 and gamma0 metadata: The two XML files per ORT delivery differ in:
 - **BackscatterMeasurementData/BackscatterMeasurement**: gamma0 vs sigma0
 - **BackscatterMeasurementData/FileName**: corresponding image filename
 - **RadiometricTerrainCorrections**: present only in the gamma0 metadata file (RTC is not applicable to the sigma0 variant)
 - All other elements and values are identical between the two files
2. Geometric accuracy (ALE): Values are provided per satellite and per observation mode, measured as end-to-end ARD ALE directly in the orthorectified product in map projection coordinates (Northing and Easting), following the CEOS-ARD NRB PFS v1.2 requirements. A positive bias indicates a shift in the positive map direction (northward / eastward); a negative bias indicates a shift in the negative direction (southward / westward).
3. Gridding convention: ORT products use a fixed UTM grid where pixel upper-left corners are aligned to exact multiples of the pixel spacing, offset by half a pixel. This ensures that all ORT acquisitions over the same area share identical pixel positions, enabling direct time-series analysis without resampling. For Stripmap, the grid spacing is 5.00 m; for Sliding Spotlight and Staring Spotlight, 1.25 m. Both spacings nest exactly (4 x 4 Sliding Spotlight/ Staring Spotlight pixels = 1 Stripmap pixel).
4. Coordinate reference system: ORT products use UTM projection only. The EPSG code and full WKT definition are both provided in the metadata. The UTM zone is determined by the scene center longitude.

3.1.3 GeoTIFF Tag

The table below describes the GeoTIFF tags present in the ORT image files (sigma0.tif and gamma0.tif) . The definition of data type is shown in the table below.

Table 3.1-3 ORT GeoTIFF Tag

| Tag / Attribute Name | Key ID | Type | Count | Description / Example |
|---------------------------|--------|-------|----------|--------------------------------|
| ImageWidth | 256 | SHORT | 1 | Number of pixels per line |
| ImageLength | 257 | SHORT | 1 | Number of lines |
| BitsPerSample | 258 | SHORT | 1 | 32 |
| Compression | 259 | SHORT | 1 | 8: Deflate |
| PhotometricInterpretation | 262 | SHORT | 1 | 1: MinIsBlack |
| SamplesPerPixel | 277 | SHORT | 1 | 1 |
| PlanarConfiguration | 284 | SHORT | 1 | 1: Contiguous (single band) |
| Software | 305 | ASCII | variable | Processing software identifier |

| Tag / Attribute Name | Key ID | Type | Count | Description / Example |
|----------------------|--------|--------|-----------------|---|
| DateTime | 306 | ASCII | 20 | File creation date and time in TIFF format "YYYY:MM:DD HH:MM:SS". Example: "2026:03:25 01:09:16" |
| Predictor | 317 | SHORT | 1 | 3: Floating-point predictor (horizontal differencing of floating-point values, improves Deflate compression ratio for float32 data) |
| TileWidth | 322 | SHORT | 1 | 512 |
| TileLength | 323 | SHORT | 1 | 512 |
| TileOffsets | 324 | LONG | Number of tiles | Byte offset to each tile |
| TileByteCounts | 325 | LONG | Number of tiles | Compressed byte count for each tile |
| SampleFormat | 339 | SHORT | 1 | 3: IEEE floating point |
| ModelPixelScaleTag | 33550 | DOUBLE | 3 | Pixel spacing in meters: (ScaleX, ScaleY, 0.0). Example: (5.0, 5.0, 0.0) for Stripmap; (1.25, 1.25, 0.0) for Spotlight |
| ModelTiepointTag | 33922 | DOUBLE | 6 | Tiepoint mapping pixel coordinates to map coordinates: (I, J, K, X, Y, Z). Maps pixel (0, 0) to its map coordinate (Easting, Northing, 0). Since GTRasterTypeGeoKey = RasterPixelIsPoint, the tiepoint refers to the centre of the upper-left pixel. Example: (0.0, 0.0, 0.0, 738337.5, 9465177.5, 0.0) |
| GeoKeyDirectoryTag | 34735 | SHORT | 4 + 4*N | GeoTIFF key directory. Contains N GeoKey entries (see GeoKey table 3.1-4) |
| GeoAsciiParamsTag | 34737 | ASCII | variable | String values referenced by GeoKeys. Example: "WGS 84 / UTM zone 50S WGS 84 " |
| GDAL_METADATA | 42112 | ASCII | variable | GDAL metadata XML block containing band statistics (STATISTICS_MAXIMUM, STATISTICS_MEAN, STATISTICS_MINIMUM, STATISTICS_STDDEV, STATISTICS_VALID_PERCENT) |
| GDAL_NODATA | 42113 | ASCII | variable | NoData pixel value. "0" (pixels with value 0.0 represent no data) |

The GeoKeyDirectoryTag (34735) contains the following GeoKeys:

Table 3.1-4 ORT GeoTIFF GeoKey Directory

| GeoKey ID | GeoKey Name | Value | Description |
|-----------|------------------------|-------------|--|
| 1024 | GtModelTypeGeoKey | 1 | ModelTypeProjected |
| 1025 | GTRasterTypeGeoKey | 2 | RasterPixelIsPoint — pixel coordinates refer to the centre of a pixel. This is consistent with the "Pixel Centre" convention declared in the XML metadata. |
| 1026 | GTCitationGeoKey | (string) | Projected CRS citation. Example: "WGS 84 / UTM zone 50S" |
| 2049 | GeogCitationGeoKey | (string) | Geographic CRS citation: "WGS 84" |
| 2054 | GeogAngularUnitsGeoKey | 9102 | Angular_Degree |
| 3072 | ProjectedCSTypeGeoKey | (EPSG code) | EPSG code of the projected coordinate reference system. Example: 32750 (WGS 84 / UTM zone 50S). The UTM zone varies per scene. |
| 3076 | ProjLinearUnitsGeoKey | 9001 | Linear_Meter |

GeoTIFF Tag Notes:

1. Pixel coordinate convention: The GeoTIFF uses **GTRasterTypeGeoKey = 2** (RasterPixelIsPoint), meaning the **ModelTiepointTag** coordinates refer to the centre of the upper-left pixel, not its corner. The GDAL metadata item AREA_OR_POINT = Point is also set consistently. When computing the upper-left corner of the raster extent, half a pixel offset must be subtracted from the tiepoint easting and added to the tiepoint northing.
2. NoData handling: The NoData value is 0.0 (float), recorded in both the GDAL_NODATA tag (42113) and in the band metadata. Pixels with value 0.0 represent areas outside the SAR image extent. Since calibrated backscatter values in linear power are strictly positive for valid measurements, 0.0 is an unambiguous NoData sentinel.
3. Band statistics: The GDAL_METADATA tag (42112) contains precomputed band statistics including maximum, mean, minimum, standard deviation, and valid pixel percentage. **STATISTICS_VALID_PERCENT** indicates the fraction of the raster extent covered by actual SAR data (the remainder being zero-fill in the rectangular GeoTIFF bounding box).

3.1.4 COG Layer Specifications

The ORT product delivery includes six tiled GeoTIFF raster files, each optimised for its specific role. The backscatter files (sigma0.tif, gamma0.tif) and their two quicklooks are valid Cloud Optimized GeoTIFFs (COG). incmap.tif and lsmap.tif are tiled GeoTIFFs that do not satisfy the COG layout constraints in this version — they will be upgraded to valid COGs in a later release. The table below summarises the raster properties of each file type.

Table 3.1-5 ORT COG File Specifications

| Property | sigma0.tif / gamma0.tif | quicklook (sigma0/gamma0) | incmap.tif | lsmmap.tif |
|----------------------------|--|--|---|---------------------------------------|
| Role | backscatter quantitative analysis | backscatter qualitative analysis and visualisation | auxiliary (local incidence angle) | auxiliary (layover/shadow mask) |
| Bands | 1 | 2 (data + alpha) | 1 | 1 |
| Data type | Float32 | Byte (UINT8) | UInt16 | Byte (UINT8) |
| Pixel values | Calibrated backscatter, linear power | Band 1: dB-encoded backscatter (see Note 2). Band 2: alpha mask (0=transparent, 255=opaque) | Incidence angle: DN x 0.01 = degrees | Classification mask |
| Compression | Deflate | Deflate | Deflate | LZW |
| Predictor | 3 (floating-point) | 1 (none) | 2 (horizontal differencing) | 2 (horizontal differencing) |
| Tile size | 512 x 512 | 512 x 512 | 512 x 512 | 512 x 512 |
| Overviews | None (see Note 1) | 5 levels (2x, 4x, 8x, 16x, 32x) | 4 levels (4x, 8x, 16x, 32x) | 5 levels (2x, 4x, 8x, 16x, 32x) |
| Overview resampling | — | Average (see Note 2) | Average | Nearest neighbour |
| NoData value | 0 | None (alpha band masks NoData) | 0 | 1 (see Note 3) |
| GTRasterType GeoKey | 2 (RasterPixelIsPoint) | 1 (RasterPixelIsArea) | 1 (RasterPixelIsArea) | 2 (RasterPixelIsPoint) |
| Scale / Offset metadata | None | Scale=0.25, Offset=-25.25 | Scale=0.01, Offset=0 | None |

COG Layer Specifications Notes:

- Backscatter files (sigma0.tif, gamma0.tif): These are the primary analysis products. No overview pyramids are included — the full-resolution tiled COG layout supports efficient partial reads via HTTP range requests for streaming access. Overviews would add ~33% to the file size with no benefit for analysis workflows.
- Quicklook files (sigma0-quicklook.tif, gamma0-quicklook.tif): These are visualisation-optimised 2-band COGs designed for display in GIS applications such as QGIS. Band 1 contains dB-encoded UINT8 data; band 2 is a Byte alpha mask (ColorInterp=Alpha) where 255=opaque (valid) and 0=transparent (NoData). No NoData value is set on the data band — NoData regions are identified exclusively via the alpha band, which GIS applications such as QGIS detect automatically. The dB encoding uses the following mapping:
 - DN = 0 to 255: backscatter in dB, where dB = DN x 0.25 - 25.25
 - This gives a range of approximately -25.25 dB (DN=0) to +38.50 dB (DN=255) in 0.25 dB steps
 - The Scale=0.25 and Offset=-25.25 band metadata allow GIS software to display values directly in dB units
 - Five overview levels (2x through 32x) provide smooth zoom navigation

- Overview pyramids are computed by averaging in the linear power domain before dB conversion; averaging directly in dB would be radiometrically incorrect and would systematically underestimate backscatter intensity at lower zoom levels. Both bands have overviews at each level.
 - Deflate compression without predictor (Predictor=1) is used — predictors are not effective for classified/quantised byte data
 - Compressed file size does not exceed 110 MB, approximately 3x smaller than the corresponding backscatter file
3. Layover/shadow mask (lsmmap.tif): Classification mask with discrete values (0, 1, 5, 17, 21, 255) and an embedded RGBA colour palette (ColorInterp=Palette). The GDAL NoData value is set to 1 (Valid Data), with alpha=0 in the colour table for that entry. This makes valid-data pixels transparent in GIS applications, so the lsmmap works as a coloured overlay where only layover, shadow, and no-data regions are visible. Five overview levels (2x through 32x) use nearest-neighbour resampling to preserve discrete class values.

3.1.5 Thumbnail Image

A thumbnail image is provided as a JPEG file for quick visual identification of the scene content. The thumbnail is derived from the gamma-naught backscatter image.

- Format: JPEG, single-band grayscale (8-bit)
- Resolution: Half the full-resolution image dimensions (2x downsampled, average resampling)
- Pixel values: Percentile-normalised dB scale. The gamma-naught linear power values are converted to decibels, then a contrast stretch is applied using the 1st and 99th percentile of the scene values. This produces an image optimised for human perception of the overall scene content.
- Map projection: North-up orientation
- Coordinate information: Not included. The JPEG is intended for visual preview only, not for geospatial analysis.

The thumbnail provides a qualitative overview of the scene suitable for cataloguing, browsing, and quick quality assessment. It is not suitable for quantitative analysis.

4. Radiometric Calibration

The following corrections are applied to the SynSpective products.

Table 4-1 Radiometric Correction

| Satellite | Mode | Antenna Pattern Correction | Range Spread Loss Correction | Incidence Angle Correction* | Calibration factor |
|-----------|--|----------------------------|------------------------------|-----------------------------|--------------------|
| StriX-α | Stripmap | | ✓ | ✓ | ✓ |
| StriX-β | Stripmap | ✓ | ✓ | ✓ | ✓ |
| StriX-β | Sliding Spotlight | ✓ | ✓ | ✓ | ✓ |
| StriX-1 | Stripmap/ Sliding Spotlight | ✓ | ✓ | ✓ | ✓ |
| StriX-2~5 | Stripmap/ Sliding Spotlight/ Staring Spotlight | ✓ | ✓ | ✓ | ✓ |

*GRD/ SR-GRD only

- SLC CEOS

The following equation will be applied to convert I and Q values to beta naught (β_{0dB}),

$$SLC: \beta_{0dB} = 10 * \log_{10} \langle I^2 + Q^2 \rangle + CF_{SLC\ CEOS}$$

To convert from β_0 to σ_0 , the incident angle correction will be applied by

$$\sigma_0 = \beta_0 * \sin(\theta),$$

where θ is the incidence angle.

- SLC SICD

Follow the NITF format document in Section 4.10 [\[2\]](#) to perform radiometric calibration.

- GRD GeoTIFF

The following equation will be applied to convert Digital Number (DN) to sigma naught (σ_0) using Calibration Factor (CF_{GRD}) in XML metadata in GRD product,

$$\sigma_0 = DN^2 / CF_{GRD}^2$$

$$\sigma_{0dB} = 10 \log_{10}(\sigma_0)$$

Note: To radiometrically calibrate GRD product, the image raster data should be used, not the quicklook raster data (*_quicklook.tif).

Note: SR-GRD product is not radiometrically calibrated. The above equation is not applied.

Note: For StriX-α Stripmap, antenna pattern correction is not applied. This results in 2~3dB uncertainty for the calibration factor when applying the above formula.

- ORT GeoTIFF

ORT products are delivered with calibrated backscatter values in linear power scale. No calibration factor needs to be applied — pixel values can be used directly:

$$\sigma_{\text{dB}} = 10 \cdot \log_{10}(\text{DN}) \text{ for sigma-naught}$$

$$\gamma_{\text{dB}} = 10 \cdot \log_{10}(\text{DN}) \text{ for gamma-naught}$$

Note: For quantitative analysis, the backscatter image files (*-sigma0.tif, *-gamma0.tif) in linear power scale should be used. The quicklook files (*-quicklook.tif) contain dB-encoded UINT8 data with embedded Scale and Offset metadata, so GIS software automatically displays calibrated dB values. Quicklook files are intended for qualitative analysis and visualization, and may be sufficient for some applications, but the linear power files are recommended for rigorous quantitative work. Quicklook encoding clips at +38.50 dB, which may be a limitation for applications involving strong reflectors (e.g., corner reflectors, metallic structures).

5. Product Release History

The product release history is shown in the following tables with the software version used to create each SAR product.

Table 5-1 Product release history

| Date | Version (SLC SICD) | Version (SLC CEOS, GRD/SR-GRD GeoTIFF+XML) | Description |
|---------------|-------------------------------|---|--|
| May 24, 2022 | v0.0.3 | v003.009 | - StriX-β is released |
| July 19, 2022 | v0.0.4 | v003.010 | - Calibration factor is added for Stripmap StriX-β |
| Sept 7, 2022 | v0.0.5 | v004.000 | - Calibration factor is added for Sliding Spotlight StriX-β - Calculation for doppler frequency (center) is updated in SLC product |
| Oct 24, 2022 | v0.0.6 | v005.000 | - Heading angle and incidence angle polynomial is added in GRD product |
| Dec 15, 2022 | v0.8.0 | v006.000 | - StriX-1 is released - Orbit state vectors are added in XML metadata in GRD product - Calculation for doppler frequency is updated in SLC product |
| Feb 27, 2023 | v0.9.0 | v007.000 | - Geolocation algorithm is updated in SLC and GRD product - ImpRespWid in SICD is fixed to match with azimuth frequency bandwidth - StriX-1 for Stripmap range sampling frequency is reduced from 187.5 MHz to 100 MHz in SLC product - linear and quadratic coefficients are set for along track Doppler rate polynomial in CEOS |
| May 15, 2023 | v0.10.0 | v008.000 | - Add resampling in the azimuth direction to reduce data size for the given resolution - Fix SFDRatePoly constant coefficient sign - UTM CRS for GRD products |
| Aug 1, 2023 | v0.11.0 | v009.000 | - Noise Equivalent Sigma Zero metadata was added to GRD and SR-GRD XML Product |
| Oct 2, 2023 | v0.12.0 | v010.000 | - Geolocation algorithm is updated in GRD product - Fixed an issue with the extent of GRD GeoTIFF raster |

| Date | Version (SLC SICD) | Version (SLC CEOS, GRD/SR-GRD GeoTIFF+XML) | Description |
|--------------|---------------------------|---|---|
| Oct 19, 2023 | v0.12.2 | v010.001 | - Fixed a minor raster alignment issue with the GRD GeoTIFF raster in Ascending observations |
| Dec 6, 2023 | v0.12.3 | v010.002 | - Fixed a bug in GRD geocoding algorithm |
| Jan 22, 2024 | v0.13.0 | v011.000 | - Updated geocoding algorithm of GRD - Updated SICD format version from 1.2.1 to 1.3.0 |
| Jan 23, 2024 | v0.13.1 | v011.000 | - Fixed a bug in processing system |
| Mar 18, 2024 | v0.13.2 | v011.000 | - Fixed a minor bug in an interface between processing library and platform pipeline |
| Apr 10, 2024 | v0.13.3 | v011.000 | - Fixed a minor bug in an interface to precise orbit |
| Apr 22, 2024 | v0.14.0 | v012.000 | - Fixed a minor bug that generated subpixel geolocation offset in GRD products |
| May 15, 2024 | v0.14.1 | v012.000 | - Support StriX-3 observations |
| Aug 1, 2024 | v0.15.0 | v013.000 | - Filled values for nominal slant range and azimuth resolutions in CEOS fields - Added fields nominal slant range and azimuth resolutions in Summary Information for CEOS product - Added metadata fields for image resolutions in XML file in GRD and SR-GRD product |
| Aug 22, 2024 | v0.15.1 | v013.000 | - Fixed a bug in the processing management system (products are not affected) |
| Sept 4, 2024 | v0.15.2 | v013.000 | - Fixed a bug in the processing management system (products are not affected) |
| Oct 2, 2024 | v0.15.3 | v013.000 | - Support Staring Spotlight observations |
| Nov 12, 2024 | v1.0.0 | v014.000 | - Support StriX-4 - Add Cloud Optimized GeoTIFF in GRD and SR-GRD product - Update focusing algorithm |
| Dec 3, 2024 | v1.1.0 | v014.000 | - Support Staring Spotlight with 0.25m Azimuth resolution - Update processing kernel for Staring Spotlight |
| Jan 15, 2025 | v1.2.0 | v014.001 | - Fixed a bug in Field No. 55 in Table 1.1-16 Signal Data Records in CEOS Product Format |

| Date | Version (SLC SICD) | Version (SLC CEOS, GRD/SR-GRD GeoTIFF+XML) | Description |
|---------------|---------------------------|---|---|
| Mar 25, 2025 | v1.3.0 | v015.000 | - Support StriX-2 - Updated a reference chirp for focusing |
| Apr 2, 2025 | v1.3.1 | v015.000 | - Fixed a bug in Staring Spotlight focusing |
| June 25, 2025 | v1.4.0 | v015.001 | - Updated timing calculation for Staring Spotlight and Sliding Spotlight - Added overlap when processing subaperture for Staring Spotlight and Sliding Spotlight - Support longer observation durations for Stripmap |
| July 15, 2025 | v1.4.1 | v015.001 | - Fixed a bug when retrieving satellite telemetry information |
| Sept 30, 2025 | v2.0.0 | v015.002 | - Switched thumbnail images pixel-intensity mapping from linear to logarithmic in SICD and CEOS - Updated sign in the offnadir angle as per product format manual - Updated heading angle calculation in GRD XML metadata |

Table 5-2 Product release history (after Dec 9, 2025)

| Date | Version (SLC SICD, GRD/SR-GRD GeoTIFF+XML) | Version (SLC CEOS) | Version (ORT GeoTIFF+XML) | Description |
|--------------|---|---------------------------|----------------------------------|--|
| Dec 9, 2025 | v2.1.0 | v015.003 | - | - Updated GRD product format - Update thumbnail images for all products |
| Dec 17, 2025 | v2.1.1 | v015.003 | - | - Reduced memory consumption when creating GRD product |
| Jan 7, 2026 | v2.1.2 | v015.003 | - | - Fixed a bug when processing calibration signals |
| Feb 10, 2026 | v2.1.3 | v015.003 | - | - Fixed a bug in an interface to an internal platform system |
| Feb 16, 2026 | v2.1.4 | v015.003 | - | - Support StriX-5 |
| Mar 11, 2026 | v2.2.0 | v015.004 | - | - Support Spotlight Enhanced product |

| Date | Version (SLC SICD, GRD/SR-GRD GeoTIFF+XML) | Version (SLC CEOS) | Version (ORT GeoTIFF+XML) | Description |
|---------------|---|---------------------------|----------------------------------|--|
| Mar 17, 2026 | v2.2.1 | v015.004 | - | - Fixed a bug in an interface to an internal platform system |
| Mar 24, 2026 | v2.2.2 | v015.004 | - | - Fixed a bug in an interface to an internal platform system |
| April 2, 2026 | v2.2.2 | v015.004 | v2026.04 | - Added ORT product |

The above versions can be confirmed in each product metadata in the table below.

Table 5-3 Software version related fields

| Product type | File | Field |
|---------------------|-------------|---|
| CEOS | VOL | Volume Descriptor Record, Field no. 12: Software release and revision number |
| SICD | nitf | SICD.ImageCreation.Application |
| GRD | XML | eop:processorVersion |
| ORT | XML | Product.ProductAttributes.DataAccess.SoftwareVersion |

Reference

[1] ALOS-2/PALSAR-2 Level 1.1/1.5/2.1/3.1 CEOS SAR Product Format Description Dec. 06, 2021.

https://www.eorc.jaxa.jp/ALOS/en/alos-2/pdf/product_format_description/PALSAR-2_xx_Format_CEOS_E_g.pdf

[2] Sensor Independent Complex Data (SICD), Volume 1, Design & Implementation Description Document, Version 1.3.0 2021-11-30.

<https://nsgreg.nga.mil/doc/view?i=5381>

[3] Sensor Independent Complex Data (SICD), Volume 2, File Format Description Document, Version 1.3.0 2021-11-30. <https://nsgreg.nga.mil/doc/view?i=5382>

[4] Sensor Independent Complex Data (SICD), Volume 3, Image Projections Description Document, Version 1.3.0 2021-11-30

<https://nsgreg.nga.mil/doc/view?i=5442>

[5] National Imagery Transmission Format (Version 2.1) for the National Imagery Transmission Format Standard, 01 May 2006.

<https://nsgreg.nga.mil/doc/view?i=4324>

[6] CEOS Analysis Ready Data for Synthetic Aperture Radar, Product Family Specification v1.2.

https://ceos.org/ard/files/PFS/SAR/v1.2/CEOS-ARD_PFS_Synthetic_Aperture_Radar_v1.2.pdf (accessed March 31, 2026)

[7] D. Small, "Flattening Gamma: Radiometric Terrain Correction for SAR Imagery," *IEEE Transactions on Geoscience and Remote Sensing*, vol. 49, no. 8, pp. 3081–3093, Aug. 2011, doi: [10.1109/TGRS.2011.2120616](https://doi.org/10.1109/TGRS.2011.2120616).